



Defect



Detect

Linux Core Dump Analysis **Accelerated**

Third Edition

Dmitry Vostokov
Software Diagnostics Services

Accelerated Linux Core Dump Analysis: Training Course Transcript with GDB and WinDbg Practice Exercises, Third Edition

Published by OpenTask, Republic of Ireland

Copyright © 2023 by OpenTask

Copyright © 2023 by Software Diagnostics Services

Copyright © 2023 by Dmitry Vostokov

All rights reserved. No part of this book may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without the publisher's prior written permission.

Product and company names mentioned in this book may be trademarks of their owners.

OpenTask books and magazines are available through booksellers and distributors worldwide.
For further information or comments, send requests to press@opentask.com.

A CIP catalog record for this book is available from the British Library.

ISBN-13: 978-1-912636-59-4 (Paperback)

Revision 3.01 (January 2023)

Contents

About the Author.....	7
Presentation Slides and Transcript.....	9
Core Dump Collection.....	31
x64 Disassembly	41
ARM64 Disassembly	53
Practice Exercises	65
Exercise 0 (x64, GDB).....	70
Exercise 0 (A64, GDB).....	72
Exercise 0 (A64, WinDbg Preview, WinDbg, Docker)	74
Exercise A1 (x64, GDB)	90
Exercise A1 (A64, GDB).....	102
Exercise A1 (A64, WinDbg Preview)	117
Exercise A2D (x64, GDB).....	134
Exercise A2D (A64, GDB)	138
Exercise A2D (A64, WinDbg Preview).....	141
Exercise A2C (x64, GDB)	145
Exercise A2C (A64, GDB).....	148
Exercise A2C (A64, WinDbg Preview)	151
Exercise A2S (x64, GDB).....	156
Exercise A2S (A64, GDB)	159
Exercise A3 (x64, GDB)	163
Exercise A3 (A64, GDB).....	166
Exercise A3 (A64, WinDbg Preview)	171
Exercise A4 (x64, GDB)	176
Exercise A4 (A64, GDB).....	182
Exercise A4 (A64, WinDbg Preview)	188
Exercise A5 (x64, GDB)	195
Exercise A5 (A64, GDB).....	198
Exercise A5 (A64, WinDbg Preview)	201
Exercise A6 (x64, GDB)	206
Exercise A6 (A64, GDB).....	221
Exercise A6 (A64, WinDbg Preview)	237
Exercise A7 (x64, GDB)	264

Exercise A8 (x64, GDB)	270
Exercise A8 (A64, GDB).....	285
Exercise A8 (A64, WinDbg Preview)	303
Exercise A9 (x64, GDB)	327
Exercise A9 (A64, GDB).....	342
Exercise A9 (A64, WinDbg Preview)	356
Exercise A10 (x64, GDB)	370
Exercise A10 (A64, GDB).....	384
Exercise A10 (A64, WinDbg Preview)	391
Exercise A11 (x64, GDB)	400
Exercise A11 (A64, GDB).....	410
Exercise A11 (A64, WinDbg Preview)	421
Exercise A12 (x64, GDB)	430
Exercise A12 (A64, GDB).....	440
Exercise A12 (A64, WinDbg Preview)	449
Exercise K1 (x64, GDB).....	459
Exercise K2 (x64, GDB).....	509
Exercise K3 (x64, GDB).....	524
Exercise K4 (x64, GDB).....	537
Exercise K5 (x64, GDB).....	562
Selected Q&A.....	571
App Source Code	579
App0	581
App1	582
App2D	583
App2C	585
App2S.....	587
App3	589
App4	591
App5	593
App6	595
App7	597
App8	599
App9	602
App10	604

App11 / App12.....	606
K2	608
K3	609
K4.....	611
K5.....	613
Selected Analysis Patterns.....	615
NULL Pointer (Data).....	617
Incomplete Stack Trace	618
Stack Trace.....	619
NULL Pointer (Code)	620
Spiking Thread	621
Dynamic Memory Corruption (Process Heap).....	622
Execution Residue (User Space)	623
Coincidental Symbolic Information	625
Stack Overflow (User Mode)	626
Divide by Zero (User Mode).....	627
Local Buffer Overflow (User Space).....	628
C++ Exception	629
Paratext	630
Active Thread.....	632
Lateral Damage.....	633
Critical Region.....	634

Exercise A1 (x64, GDB)

Goal: Learn how to list stack traces, disassemble functions, check their correctness, dump data, get environment.

Patterns: Manual Dump (Process); Stack Trace; Stack Trace Collection; Annotated Disassembly; Paratext; Not My Version; Environment Hint.

1. Load a core dump *App1.core.253* and *App1* executable from the x64/App1 directory:

```
~/ALCDA2/x64/App1$ gdb -c App1.core.253 -se App1
GNU gdb (Debian 8.2.1-2+b3) 8.2.1
Copyright (C) 2018 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<http://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from App1...done.
[New LWP 253]
[New LWP 254]
[New LWP 255]
[New LWP 256]
[New LWP 257]
[New LWP 258]
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Core was generated by `./App1'.
#0 0x0000000000441a10 in nanosleep ()
[Current thread is 1 (Thread 0x21b3880 (LWP 253))]
```

2. Set logging to a file in case of lengthy output from some commands:

```
(gdb) set logging on App1.log
Copying output to App1.log.
```

3. List all threads:

```
(gdb) info threads
Id  Target Id          Frame
* 1   Thread 0x21b3880 (LWP 253)  0x0000000000441a10 in nanosleep ()
  2   Thread 0x7f0fc16fb700 (LWP 254) 0x0000000000441a10 in nanosleep ()
  3   Thread 0x7f0fc0efa700 (LWP 255) 0x0000000000441a10 in nanosleep ()
  4   Thread 0x7f0fc06f9700 (LWP 256) 0x0000000000441a10 in nanosleep ()
  5   Thread 0x7f0fbfef8700 (LWP 257) 0x0000000000441a10 in nanosleep ()
  6   Thread 0x7f0fbf6f7700 (LWP 258) 0x0000000000441a10 in nanosleep ()
```

4. Get the current thread stack trace:

```
(gdb) bt
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401d92 in main () at pthread_create.c:688
```

5. Get all thread stack traces:

```
(gdb) thread apply all bt

Thread 6 (Thread 0x7f0fbf6f7700 (LWP 258)):
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401cb7 in bar_five ()
#3 0x0000000000401cc8 in foo_five ()
#4 0x0000000000401ce1 in thread_five ()
#5 0x00000000004030d3 in start_thread (arg=<optimized out>) at pthread_create.c:486
#6 0x000000000044426f in clone ()

Thread 5 (Thread 0x7f0fbfef8700 (LWP 257)):
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401c78 in bar_four () at pthread_create.c:688
#3 0x0000000000401c89 in foo_four () at pthread_create.c:688
#4 0x0000000000401ca2 in thread_four () at pthread_create.c:688
#5 0x00000000004030d3 in start_thread (arg=<optimized out>) at pthread_create.c:486
#6 0x000000000044426f in clone ()

Thread 4 (Thread 0x7f0fc06f9700 (LWP 256)):
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401c39 in bar_three () at pthread_create.c:688
#3 0x0000000000401c4a in foo_three () at pthread_create.c:688
#4 0x0000000000401c63 in thread_three () at pthread_create.c:688
#5 0x00000000004030d3 in start_thread (arg=<optimized out>) at pthread_create.c:486
#6 0x000000000044426f in clone ()

Thread 3 (Thread 0x7f0fc0efa700 (LWP 255)):
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401bfa in bar_two () at pthread_create.c:688
#3 0x0000000000401c0b in foo_two () at pthread_create.c:688
#4 0x0000000000401c24 in thread_two () at pthread_create.c:688
#5 0x00000000004030d3 in start_thread (arg=<optimized out>) at pthread_create.c:486
#6 0x000000000044426f in clone ()

Thread 2 (Thread 0x7f0fc16fb700 (LWP 254)):
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401bbb in bar_one () at pthread_create.c:688
#3 0x0000000000401bcc in foo_one () at pthread_create.c:688
#4 0x0000000000401be5 in thread_one () at pthread_create.c:688
#5 0x00000000004030d3 in start_thread (arg=<optimized out>) at pthread_create.c:486
#6 0x000000000044426f in clone ()

Thread 1 (Thread 0x21b3880 (LWP 253)):
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401d92 in main () at pthread_create.c:688
```

6. Switch to thread #2 and get its stack trace:

```
(gdb) thread 2
[Switching to thread 2 (Thread 0x7f0fc16fb700 (LWP 254))]
#0 0x0000000000441a10 in nanosleep ()

(gdb) bt
#0 0x0000000000441a10 in nanosleep ()
#1 0x000000000044199a in sleep ()
#2 0x0000000000401bbb in bar_one () at pthread_create.c:688
#3 0x0000000000401bcc in foo_one () at pthread_create.c:688
#4 0x0000000000401be5 in thread_one () at pthread_create.c:688
#5 0x00000000004030d3 in start_thread (arg=<optimized out>) at pthread_create.c:486
#6 0x000000000044426f in clone ()
```

```
(gdb) info threads
Id Target Id          Frame
 1 Thread 0x21b3880 (LWP 253) 0x0000000000441a10 in nanosleep ()
* 2 Thread 0x7f0fc16fb700 (LWP 254) 0x0000000000441a10 in nanosleep ()
 3 Thread 0x7f0fc0efa700 (LWP 255) 0x0000000000441a10 in nanosleep ()
 4 Thread 0x7f0fc06f9700 (LWP 256) 0x0000000000441a10 in nanosleep ()
 5 Thread 0x7f0fbfef8700 (LWP 257) 0x0000000000441a10 in nanosleep ()
 6 Thread 0x7f0fbf6f7700 (LWP 258) 0x0000000000441a10 in nanosleep ()
```

7. Check that *bar_one* called the *sleep* function by comparing the return address on the call stack from the disassembly output:

```
(gdb) disassemble bar_one
Dump of assembler code for function bar_one:
0x0000000000401bad <+0>:    push   %rbp
0x0000000000401bae <+1>:    mov    %rsp,%rbp
0x0000000000401bb1 <+4>:    mov    $0xffffffff,%edi
0x0000000000401bb6 <+9>:    callq  0x441960 <sleep>
0x0000000000401bbb <+14>:   nop
0x0000000000401bbc <+15>:   pop    %rbp
0x0000000000401bbd <+16>:   retq
End of assembler dump.
```

We see that the address in the stack trace for the *bar_one* function is the address to return to after calling the *sleep* function.

8. Compare with Intel disassembly flavor:

```
(gdb) set disassembly-flavor intel
(gdb) disassemble bar_one
Dump of assembler code for function bar_one:
0x0000000000401bad <+0>:    push   rbp
0x0000000000401bae <+1>:    mov    rbp,rs
0x0000000000401bb1 <+4>:    mov    edi,0xffffffff
0x0000000000401bb6 <+9>:    call   0x441960 <sleep>
0x0000000000401bbb <+14>:   nop
0x0000000000401bbc <+15>:   pop    rbp
0x0000000000401bbd <+16>:   ret
End of assembler dump.
```

```
(gdb) set disassembly-flavor att
```

9. Get App1 data section from the output of pmap (App1.pmap.253):

```
(gdb) ^Z
[2]+ Stopped                  gdb -c App1.core.253 -se App1

~/ALCDA2/x64/App1$ cat App1.pmap.253
253: ./App1
0000000000400000      4K r---- App1
0000000000401000      588K r-x-- App1
0000000000494000      156K r---- App1
00000000004bc000      24K rw--- App1
00000000004c2000      24K rw--- [ anon ]
000000000021b3000      140K rw--- [ anon ]
00007f0fbeef7000      4K ----- [ anon ]
00007f0fbeef8000      8192K rw--- [ anon ]
00007f0fbf6f8000      4K ----- [ anon ]
00007f0fbf6f9000      8192K rw--- [ anon ]
00007f0fbfef9000      4K ----- [ anon ]
00007f0fbfef9000      8192K rw--- [ anon ]
00007f0fc06fa000      4K ----- [ anon ]
00007f0fc06fb000      8192K rw--- [ anon ]
00007f0fc0efb000      4K ----- [ anon ]
00007f0fc0efc000      8192K rw--- [ anon ]
00007ffd4545000      132K rw--- [ stack ]
00007ffd45c6000      16K r---- [ anon ]
00007ffd45ca000      4K r-x-- [ anon ]
total                 42068K
```

```
~/ALCDA2/x64/App1$ fg
gdb -c App1.core.253 -se App1
```

```
(gdb)
```

10. Compare with the section information in the core dump:

```
(gdb) maintenance info sections
Exec file:
`/home/coredump/ALCDA2/x64/App1/App1', file type elf64-x86-64.
[0] 0x00400200->0x00400220 at 0x00000200: .note.ABI-tag ALLOC LOAD READONLY DATA HAS_CONTENTS
[1] 0x00400220->0x00400244 at 0x00000220: .note.gnu.build-id ALLOC LOAD READONLY DATA HAS_CONTENTS
[2] 0x00400248->0x004004d0 at 0x00000248: .rela.plt ALLOC LOAD READONLY DATA HAS_CONTENTS
[3] 0x00401000->0x00401017 at 0x00001000: .init ALLOC LOAD READONLY CODE HAS_CONTENTS
[4] 0x00401018->0x004010f0 at 0x00001018: .plt ALLOC LOAD READONLY CODE HAS_CONTENTS
[5] 0x004010f0->0x004933d0 at 0x000010f0: .text ALLOC LOAD READONLY CODE HAS_CONTENTS
[6] 0x004933d0->0x00493f77 at 0x000933d0: __libc_freeres_fn ALLOC LOAD READONLY CODE HAS_CONTENTS
[7] 0x00493f78->0x00493f81 at 0x00093f78: .fini ALLOC LOAD READONLY CODE HAS_CONTENTS
[8] 0x00494000->0x004ae73c at 0x00094000: .rodata ALLOC LOAD READONLY DATA HAS_CONTENTS
[9] 0x004ae740->0x004bab50 at 0x000ae740: .eh_frame ALLOC LOAD READONLY DATA HAS_CONTENTS
[10] 0x004bab50->0x004babfc at 0x000bab50: .gcc_except_table ALLOC LOAD READONLY DATA HAS_CONTENTS
[11] 0x004bc0b0->0x004bc0d8 at 0x000bb0b0: .tdata ALLOC LOAD DATA HAS_CONTENTS
[12] 0x004bc0d8->0x004bc120 at 0x000bb0d8: .tbss ALLOC
[13] 0x004bc0d8->0x004bc0e0 at 0x000bb0d8: .preinit_array ALLOC LOAD DATA HAS_CONTENTS
[14] 0x004bc0e0->0x004bc0f0 at 0x000bb0e0: .init_array ALLOC LOAD DATA HAS_CONTENTS
[15] 0x004bc0f0->0x004bc100 at 0x000bb0f0: .fini_array ALLOC LOAD DATA HAS_CONTENTS
[16] 0x004bc100->0x004beef4 at 0x000bb100: .data.rel.ro ALLOC LOAD DATA HAS_CONTENTS
[17] 0x004beef8->0x004bf000 at 0x000bdef8: .got ALLOC LOAD DATA HAS_CONTENTS
[18] 0x004bf000->0x004bf0f0 at 0x000be000: .got.plt ALLOC LOAD DATA HAS_CONTENTS
[19] 0x004bf100->0x004c0c30 at 0x000be100: .data ALLOC LOAD DATA HAS_CONTENTS
[20] 0x004c0c30->0x004c0c90 at 0x000bfc30: __libc_subfreeres ALLOC LOAD DATA HAS_CONTENTS
[21] 0x004c0ca0->0x004c1408 at 0x000bfca0: __libc_IO_vtables ALLOC LOAD DATA HAS_CONTENTS
[22] 0x004c1408->0x004c1410 at 0x000c0408: __libc_atexit ALLOC LOAD DATA HAS_CONTENTS
[23] 0x004c1420->0x004c7528 at 0x000c0410: .bss ALLOC
```

```

[24] 0x004c7528->0x004c7558 at 0x000c0410: __libc_freeeres_ptrs ALLOC
[25] 0x00000000->0x00000038 at 0x000c0410: .comment READONLY HAS_CONTENTS
[26] 0x00000000->0x00000420 at 0x000c0450: .debug_aranges READONLY HAS_CONTENTS
[27] 0x00000000->0x000372ad at 0x000c0870: .debug_info READONLY HAS_CONTENTS
[28] 0x00000000->0x000057e8 at 0x000f7b1d: .debug_abbrev READONLY HAS_CONTENTS
[29] 0x00000000->0x0000aa2b at 0x000fd305: .debug_line READONLY HAS_CONTENTS
[30] 0x00000000->0x00004d08 at 0x00107d30: .debug_str READONLY HAS_CONTENTS
[31] 0x00000000->0x0000d4b8 at 0x0010ca38: .debug_loc READONLY HAS_CONTENTS
[32] 0x00000000->0x000024c0 at 0x00119ef0: .debug_ranges READONLY HAS_CONTENTS

Core file:
`/home/coredump/ALCDA2/x64/App1/App1.core.253', file type elf64-x86-64.

[0] 0x00000000->0x00002ec4 at 0x000003f8: note0 READONLY HAS_CONTENTS
[1] 0x00000000->0x000000d8 at 0x00000518: .reg/253 HAS_CONTENTS
[2] 0x00000000->0x000000d8 at 0x00000518: .reg HAS_CONTENTS
[3] 0x00000000->0x00000200 at 0x0000060c: .reg2/253 HAS_CONTENTS
[4] 0x00000000->0x00000200 at 0x0000060c: .reg2 HAS_CONTENTS
[5] 0x00000000->0x00000340 at 0x00000820: .reg-xstate/253 HAS_CONTENTS
[6] 0x00000000->0x00000340 at 0x00000820: .reg-xstate HAS_CONTENTS
[7] 0x00000000->0x00000080 at 0x00000b74: .note.linuxcore.siginfo/253 HAS_CONTENTS
[8] 0x00000000->0x00000080 at 0x00000b74: .note.linuxcore.siginfo HAS_CONTENTS
[9] 0x00000000->0x000000d8 at 0x00000c78: .reg/254 HAS_CONTENTS
[10] 0x00000000->0x00000200 at 0x00000d6c: .reg2/254 HAS_CONTENTS
[11] 0x00000000->0x00000340 at 0x00000f80: .reg-xstate/254 HAS_CONTENTS
[12] 0x00000000->0x00000080 at 0x000012d4: .note.linuxcore.siginfo/254 HAS_CONTENTS
[13] 0x00000000->0x000000d8 at 0x000013d8: .reg/255 HAS_CONTENTS
[14] 0x00000000->0x00000200 at 0x000014cc: .reg2/255 HAS_CONTENTS
[15] 0x00000000->0x00000340 at 0x000016e0: .reg-xstate/255 HAS_CONTENTS
[16] 0x00000000->0x00000080 at 0x00001a34: .note.linuxcore.siginfo/255 HAS_CONTENTS
[17] 0x00000000->0x000000d8 at 0x00001b38: .reg/256 HAS_CONTENTS
[18] 0x00000000->0x00000200 at 0x00001c2c: .reg2/256 HAS_CONTENTS
[19] 0x00000000->0x00000340 at 0x00001e40: .reg-xstate/256 HAS_CONTENTS

--Type <RET> for more, q to quit, c to continue without paging--
[20] 0x00000000->0x00000080 at 0x00002194: .note.linuxcore.siginfo/256 HAS_CONTENTS
[21] 0x00000000->0x000000d8 at 0x00002298: .reg/257 HAS_CONTENTS
[22] 0x00000000->0x00000200 at 0x0000238c: .reg2/257 HAS_CONTENTS
[23] 0x00000000->0x00000340 at 0x000025a0: .reg-xstate/257 HAS_CONTENTS
[24] 0x00000000->0x00000080 at 0x000028f4: .note.linuxcore.siginfo/257 HAS_CONTENTS
[25] 0x00000000->0x000000d8 at 0x000029f8: .reg/258 HAS_CONTENTS
[26] 0x00000000->0x00000200 at 0x00002aecd: .reg2/258 HAS_CONTENTS
[27] 0x00000000->0x00000340 at 0x00002d00: .reg-xstate/258 HAS_CONTENTS
[28] 0x00000000->0x00000080 at 0x00003054: .note.linuxcore.siginfo/258 HAS_CONTENTS
[29] 0x00000000->0x00000140 at 0x000030e8: .auxv HAS_CONTENTS
[30] 0x00000000->0x0000007e at 0x0000323c: .note.linuxcore.file/258 HAS_CONTENTS
[31] 0x00000000->0x0000007e at 0x0000323c: .note.linuxcore.file HAS_CONTENTS
[32] 0x00401000->0x00494000 at 0x000032bc: load1 ALLOC LOAD READONLY CODE HAS_CONTENTS
[33] 0x004bc000->0x004c2000 at 0x000962bc: load2 ALLOC LOAD HAS_CONTENTS
[34] 0x004c2000->0x004c8000 at 0x0009c2bc: load3 ALLOC LOAD HAS_CONTENTS
[35] 0x021b3000->0x021d6000 at 0x000a22bc: load4 ALLOC LOAD HAS_CONTENTS
[36] 0x7f0fbeef7000->0x7f0fbeef8000 at 0x000c52bc: load5 ALLOC LOAD READONLY HAS_CONTENTS
[37] 0x7f0fbeef8000->0x7f0fb6f8000 at 0x000c62bc: load6 ALLOC LOAD HAS_CONTENTS
[38] 0x7f0fb6f8000->0x7f0fb6f9000 at 0x008c62bc: load7 ALLOC LOAD READONLY HAS_CONTENTS
[39] 0x7f0fb6f9000->0x7f0fbfef9000 at 0x008c72bc: load8 ALLOC LOAD HAS_CONTENTS
[40] 0x7f0fbfef9000->0x7f0fbfef000 at 0x010c72bc: load9 ALLOC LOAD READONLY HAS_CONTENTS
[41] 0x7f0fbfef000->0x7f0fc06fa000 at 0x010c82bc: load10 ALLOC LOAD HAS_CONTENTS
[42] 0x7f0fc06fa000->0x7f0fc06fb000 at 0x018c82bc: load11 ALLOC LOAD READONLY HAS_CONTENTS
[43] 0x7f0fc06fb000->0x7f0fc0efb000 at 0x018c92bc: load12 ALLOC LOAD HAS_CONTENTS
[44] 0x7f0fc0efb000->0x7f0fc0efc000 at 0x020c92bc: load13 ALLOC LOAD READONLY HAS_CONTENTS
[45] 0x7f0fc0efc000->0x7f0fc16fc000 at 0x020ca2bc: load14 ALLOC LOAD HAS_CONTENTS
[46] 0x7ffdf4545000->0x7ffdf4566000 at 0x028ca2bc: load15 ALLOC LOAD HAS_CONTENTS
[47] 0x7ffdf45ca000->0x7ffdf45cb000 at 0x028eb2bc: load16 ALLOC LOAD READONLY CODE HAS_CONTENTS

```

11. Dump .data section with possible symbolic information:

```
(gdb) x/256a 0x004bf100
0x4bf100: 0x0 0x0
0x4bf110 <__nptl_nthreads>: 0x6 0x0
0x4bf120 <stack_used>: 0x7f0fbf6f79c0 0x7f0fc16fb9c0
0x4bf130 <stack_cache>: 0x4bf130 <stack_cache> 0x4bf130 <stack_cache>
0x4bf140 <_sched_fifo_max_prio>: 0xfffffffffffffff 0x0
0x4bf150 <_elision_aconf>: 0x300000003 0x3000000000
0x4bf160 <_dl_tls_static_size>: 0x1180 0x494a88 <_nl_default_default_domain>
0x4bf170 <_exit_funcs>: 0x4c5a80 <initial> 0x493040 <_gcc_personality_v0>
0x4bf180 <_IO_list_all>: 0x4bf1a0 <_IO_2_1_stderr_> 0x0
0x4bf190: 0x0 0x0
0x4bf1a0 <_IO_2_1_stderr_>: 0xfbcd2086 0x0
0x4bf1b0 <_IO_2_1_stderr_+16>: 0x0 0x0
0x4bf1c0 <_IO_2_1_stderr_+32>: 0x0 0x0
0x4bf1d0 <_IO_2_1_stderr_+48>: 0x0 0x0
0x4bf1e0 <_IO_2_1_stderr_+64>: 0x0 0x0
0x4bf1f0 <_IO_2_1_stderr_+80>: 0x0 0x0
0x4bf200 <_IO_2_1_stderr_+96>: 0x0 0x4bf3c0 <_IO_2_1_stdout_>
0x4bf210 <_IO_2_1_stderr_+112>: 0x8000000002 0xfffffffffffffff
0x4bf220 <_IO_2_1_stderr_+128>: 0x0 0x4c5ec0 <_IO_stdfile_2_lock>
0x4bf230 <_IO_2_1_stderr_+144>: 0xfffffffffffffff 0x0
0x4bf240 <_IO_2_1_stderr_+160>: 0x4bf280 <_IO_wide_data_2> 0x0
0x4bf250 <_IO_2_1_stderr_+176>: 0x0 0x0
0x4bf260 <_IO_2_1_stderr_+192>: 0x0 0x0
0x4bf270 <_IO_2_1_stderr_+208>: 0x0 0x4c1060 <_IO_file_jumps>
0x4bf280 <_IO_wide_data_2>: 0x0 0x0
0x4bf290 <_IO_wide_data_2+16>: 0x0 0x0
0x4bf2a0 <_IO_wide_data_2+32>: 0x0 0x0
0x4bf2b0 <_IO_wide_data_2+48>: 0x0 0x0
0x4bf2c0 <_IO_wide_data_2+64>: 0x0 0x0
0x4bf2d0 <_IO_wide_data_2+80>: 0x0 0x0
0x4bf2e0 <_IO_wide_data_2+96>: 0x0 0x0
0x4bf2f0 <_IO_wide_data_2+112>: 0x0 0x0
0x4bf300 <_IO_wide_data_2+128>: 0x0 0x0
0x4bf310 <_IO_wide_data_2+144>: 0x0 0x0
0x4bf320 <_IO_wide_data_2+160>: 0x0 0x0
0x4bf330 <_IO_wide_data_2+176>: 0x0 0x0
0x4bf340 <_IO_wide_data_2+192>: 0x0 0x0
0x4bf350 <_IO_wide_data_2+208>: 0x0 0x0
0x4bf360 <_IO_wide_data_2+224>: 0x0 0x0
0x4bf370 <_IO_wide_data_2+240>: 0x0 0x0
0x4bf380 <_IO_wide_data_2+256>: 0x0 0x0
0x4bf390 <_IO_wide_data_2+272>: 0x0 0x0
0x4bf3a0 <_IO_wide_data_2+288>: 0x0 0x0
0x4bf3b0 <_IO_wide_data_2+304>: 0x4c0e20 <_IO_wfile_jumps> 0x0
0x4bf3c0 <_IO_2_1_stdout_>: 0xfbcd2084 0x0
0x4bf3d0 <_IO_2_1_stdout_+16>: 0x0 0x0
0x4bf3e0 <_IO_2_1_stdout_+32>: 0x0 0x0
0x4bf3f0 <_IO_2_1_stdout_+48>: 0x0 0x0
0x4bf400 <_IO_2_1_stdout_+64>: 0x0 0x0
0x4bf410 <_IO_2_1_stdout_+80>: 0x0 0x0
0x4bf420 <_IO_2_1_stdout_+96>: 0x0 0x4bf5e0 <_IO_2_1_stdin_>
0x4bf430 <_IO_2_1_stdout_+112>: 0x8000000001 0xfffffffffffffff
0x4bf440 <_IO_2_1_stdout_+128>: 0x0 0x4c5ed0 <_IO_stdfile_1_lock>
0x4bf450 <_IO_2_1_stdout_+144>: 0xfffffffffffffff 0x0
0x4bf460 <_IO_2_1_stdout_+160>: 0x4bf4a0 <_IO_wide_data_1> 0x0
0x4bf470 <_IO_2_1_stdout_+176>: 0x0 0x0
0x4bf480 <_IO_2_1_stdout_+192>: 0x0 0x0
```

```
--Type <RET> for more, q to quit, c to continue without paging--
0x4bf490 <_IO_2_1_stdout_+208>: 0x0      0x4c1060 <_IO_file_jumps>
0x4bf4a0 <_IO_wide_data_1>:    0x0      0x0
0x4bf4b0 <_IO_wide_data_1+16>: 0x0      0x0
0x4bf4c0 <_IO_wide_data_1+32>: 0x0      0x0
0x4bf4d0 <_IO_wide_data_1+48>: 0x0      0x0
0x4bf4e0 <_IO_wide_data_1+64>: 0x0      0x0
0x4bf4f0 <_IO_wide_data_1+80>: 0x0      0x0
0x4bf500 <_IO_wide_data_1+96>: 0x0      0x0
0x4bf510 <_IO_wide_data_1+112>: 0x0      0x0
0x4bf520 <_IO_wide_data_1+128>: 0x0      0x0
0x4bf530 <_IO_wide_data_1+144>: 0x0      0x0
0x4bf540 <_IO_wide_data_1+160>: 0x0      0x0
0x4bf550 <_IO_wide_data_1+176>: 0x0      0x0
0x4bf560 <_IO_wide_data_1+192>: 0x0      0x0
0x4bf570 <_IO_wide_data_1+208>: 0x0      0x0
0x4bf580 <_IO_wide_data_1+224>: 0x0      0x0
0x4bf590 <_IO_wide_data_1+240>: 0x0      0x0
0x4bf5a0 <_IO_wide_data_1+256>: 0x0      0x0
0x4bf5b0 <_IO_wide_data_1+272>: 0x0      0x0
0x4bf5c0 <_IO_wide_data_1+288>: 0x0      0x0
0x4bf5d0 <_IO_wide_data_1+304>: 0x4c0e20 <_IO_wfile_jumps>      0x0
0x4bf5e0 <_IO_2_1_stdin_>:    0xfbdb2088      0x0
0x4bf5f0 <_IO_2_1_stdin_+16>: 0x0      0x0
0x4bf600 <_IO_2_1_stdin_+32>: 0x0      0x0
0x4bf610 <_IO_2_1_stdin_+48>: 0x0      0x0
0x4bf620 <_IO_2_1_stdin_+64>: 0x0      0x0
0x4bf630 <_IO_2_1_stdin_+80>: 0x0      0x0
0x4bf640 <_IO_2_1_stdin_+96>: 0x0      0x0
0x4bf650 <_IO_2_1_stdin_+112>: 0x8000000000      0xffffffffffffffff
0x4bf660 <_IO_2_1_stdin_+128>: 0x0      0x4c5ee0 <_IO_stdfile_0_lock>
0x4bf670 <_IO_2_1_stdin_+144>: 0xfffffffffffffff      0x0
0x4bf680 <_IO_2_1_stdin_+160>: 0x4bf6c0 <_IO_wide_data_0>      0x0
0x4bf690 <_IO_2_1_stdin_+176>: 0x0      0x0
0x4bf6a0 <_IO_2_1_stdin_+192>: 0x0      0x0
0x4bf6b0 <_IO_2_1_stdin_+208>: 0x0      0x4c1060 <_IO_file_jumps>
0x4bf6c0 <_IO_wide_data_0_>:    0x0      0x0
0x4bf6d0 <_IO_wide_data_0+16>: 0x0      0x0
0x4bf6e0 <_IO_wide_data_0+32>: 0x0      0x0
0x4bf6f0 <_IO_wide_data_0+48>: 0x0      0x0
0x4bf700 <_IO_wide_data_0+64>: 0x0      0x0
0x4bf710 <_IO_wide_data_0+80>: 0x0      0x0
0x4bf720 <_IO_wide_data_0+96>: 0x0      0x0
0x4bf730 <_IO_wide_data_0+112>: 0x0      0x0
0x4bf740 <_IO_wide_data_0+128>: 0x0      0x0
0x4bf750 <_IO_wide_data_0+144>: 0x0      0x0
0x4bf760 <_IO_wide_data_0+160>: 0x0      0x0
0x4bf770 <_IO_wide_data_0+176>: 0x0      0x0
0x4bf780 <_IO_wide_data_0+192>: 0x0      0x0
0x4bf790 <_IO_wide_data_0+208>: 0x0      0x0
0x4bf7a0 <_IO_wide_data_0+224>: 0x0      0x0
0x4bf7b0 <_IO_wide_data_0+240>: 0x0      0x0
0x4bf7c0 <_IO_wide_data_0+256>: 0x0      0x0
0x4bf7d0 <_IO_wide_data_0+272>: 0x0      0x0
0x4bf7e0 <_IO_wide_data_0+288>: 0x0      0x0
0x4bf7f0 <_IO_wide_data_0+304>: 0x4c0e20 <_IO_wfile_jumps>      0x4bf1a0 <_IO_2_1_stderr_>
0x4bf800 <stdout_>:      0x4bf3c0 <_IO_2_1_stdout_>      0x4bf5e0 <_IO_2_1_stdin_>
0x4bf810:      0x0      0x0
--Type <RET> for more, q to quit, c to continue without paging--
0x4bf820 <may_shrink_heap.11591>:      0x1fffffff      0x1
```

```

0x4bf830:      0x0      0x0
0x4bf840 <mp_>: 0x20000 0x20000
0x4bf850 <mp_+16>: 0x20000 0x8
0x4bf860 <mp_+32>: 0x0      0x1000000000000000
0x4bf870 <mp_+48>: 0x0      0x0
0x4bf880 <mp_+64>: 0x0      0x21b41c0
0x4bf890 <mp_+80>: 0x40     0x408
0x4bf8a0 <mp_+96>: 0x7      0x0
0x4bf8b0:      0x0      0x0
0x4bf8c0 <__memalign_hook>: 0x41aad0 <memalign_hook_ini> 0x41b0e0 <realloc_hook_ini>
0x4bf8d0 <__malloc_hook>: 0x0      0x0
0x4bf8e0 <main_arena>: 0x0      0x0
0x4bf8f0 <main_arena+16>: 0x0      0x0

```

The output is in the following format:

```
address:    value1    value2
```

Because the size of each value is 8 bytes, the next address is +16 bytes or +10_{hex}. The addresses can have associated symbolic names:

```
address <name>:  value1  value2
```

For example, from the output above:

```
0x4bf110 <__nptl_nthreads>: 0x6      0x0
```

Each value may also have an associated symbolic value:

```
address <name>:  value1 <name1>    value2
```

For example, from the output above:

```
0x4bf8c0 <__memalign_hook>: 0x41aad0 <memalign_hook_ini> 0x41b0e0 <realloc_hook_ini>
```

12. Explore the contents of memory pointed to by `__nptl_nthreads`, `_nl_default_default_domain`, and `__memalign_hook` addresses (`/x` is for hex, `/d` is for decimals, `/u` is for unsigned decimals, `/g` is for 64-bit values, `/w` is for 32-bit values, `/h` is for 16-bit values, `/b` is for byte values, `/a` is for addresses, `/c` and `/s` are for chars and strings):

```
(gdb) x/d 0x4bf110
0x4bf110 <__nptl_nthreads>: 6
```

```
(gdb) x/u &__nptl_nthreads
0x4bf110 <__nptl_nthreads>: 6
```

```
(gdb) x/wx 0x4bf110
0x4bf110 <__nptl_nthreads>: 0x00000006
```

```
(gdb) x/gx 0x4bf110
0x4bf110 <__nptl_nthreads>: 0x0000000000000006
```

```
(gdb) x/hx 0x4bf110
0x4bf110 <__nptl_nthreads>: 0x0006
```

```
(gdb) x/bx 0x4bf110
0x4bf110 <__nptl_nthreads>: 0x06
```

```
(gdb) x/2a 0x4bf160
0x4bf160 <_dl_tls_static_size>: 0x1180 0x494a88 <_nl_default_default_domain>
```

Note: Some symbols and addresses (for example, **0x494a88**) belong to read-only sections of executable image. If GDB refuses to read them you may need to run this command:

```
set trust-readonly-sections on
```

```
(gdb) x/a &_nl_default_default_domain
0x494a88 <_nl_default_default_domain>: 0x736567617373656d
```

```
(gdb) set trust-readonly-sections on
```

```
(gdb) x/a 0x494a88
0x494a88 <_nl_default_default_domain>: 0x736567617373656d
```

```
(gdb) x/s 0x494a88
0x494a88 <_nl_default_default_domain>: "messages"
```

```
(gdb) x/10a 0x494a88
0x494a88 <_nl_default_default_domain>: 0x736567617373656d      0x6c006f6c00756c00
0x494a98:    0x786c00586c0069      0x7273752f00656372
0x494aa8:    0x6c2f65726168732f      0x656c61636f
0x494ab8 <aliasfile.10131>:    0x2e656c61636f6c2f      0x7361696c61
0x494ac8:    0x0      0x0
```

```
(gdb) x/8c 0x494a88
0x494a88 <_nl_default_default_domain>: 109 'm' 101 'e' 115 's' 115 's' 97 'a' 103 'g' 101 'e'
115 's'
```

```
(gdb) x/10s 0x494a88
0x494a88 <_nl_default_default_domain>: "messages"
0x494a91:    "lu"
0x494a94:    "lo"
0x494a97:    "li"
0x494a9a:    "lx"
0x494a9d:    "lx"
0x494aa0:    "rce"
0x494aa4:    "/usr/share/locale"
0x494ab6:    ""
0x494ab7:    ""
```

Note: We see that a hook function is installed for *memalign* but not *malloc*. Please find the following documentation for hook functions here:

https://www.gnu.org/software/libc/manual/html_node/Hooks-for-Malloc.html

13. Explore the contents of memory pointed to by *environ* variable address:

```
(gdb) x/a &environ
0x4c5f48 <environ>: 0x7ffd45637f8
```

```
(gdb) x/10a 0x7ffd45637f8
0x7ffd45637f8: 0x7ffd4565756 0x7ffd4565766
0x7ffd4563808: 0x7ffd456577d 0x7ffd4565794
0x7ffd4563818: 0x7ffd45657a9 0x7ffd45657c7
0x7ffd4563828: 0x7ffd45657d8 0x7ffd45657f3
0x7ffd4563838: 0x7ffd45657fe 0x7ffd4565812
```

```
(gdb) x/10s 0x7ffdf4565756
0x7ffdf4565756: "SHELL=/bin/bash"
0x7ffdf4565766: "HISTCONTROL=ignoreboth"
0x7ffdf456577d: "WSL_DISTRO_NAME=Debian"
0x7ffdf4565794: "NAME=DESKTOP-IS6V2L0"
0x7ffdf45657a9: "PWD=/home/coredump/ALCDA/App1"
0x7ffdf45657c7: "LOGNAME=coredump"
0x7ffdf45657d8: "MC_TMPDIR=/tmp/mc-coredump"
0x7ffdf45657f3: "MC_SID=192"
0x7ffdf45657fe: "HOME=/home/coredump"
0x7ffdf4565812: "LANG=en_US.UTF-8"
```

14. Now we look at how to perform a memory search. It is not possible to search in the entire virtual memory, only in the valid regions.

```
(gdb) find /g 0x004bc000, 0x004d2000, 6
0x4bd5f8 <_nl_C_LC_NUMERIC+56>
0x4be880 <tunable_list+928>
0x4bea40 <dyn_temp.10655+32>
0x4bf110 <__nptl_nthreads>
warning: Unable to access 16000 bytes of target memory at 0x4c6e18, halting search.
4 patterns found.
```

```
(gdb) x/gd 0x4bf110
0x4bf110 <__nptl_nthreads>: 6
```

```
(gdb) x/s 0x7ffdf4565756
0x7ffdf4565756: "SHELL=/bin/bash"
```

```
(gdb) find 0x7ffdf4565756, +100, "bash"
0x7ffdf4565761
1 pattern found.
```

Note: "bash" is considered a null-terminated array of characters for the search. To search for a string sequence without a null terminator, use a sequence of characters:

```
(gdb) find 0x7ffdf4565756, +100, "bin"
Pattern not found.

(gdb) find 0x7ffdf4565756, +100, 'b', 'i', 'n'
0x7ffdf456575d
1 pattern found.
```

15. Get the list of loaded modules:

```
(gdb) info sharedlibrary
No shared libraries loaded at this time.
```

Note: We don't see any shared libraries because they were statically linked. We also created the version of a dynamically linked *App1.shared* executable. If we load its core dump *App1.shared.core.275*, we see the list of shared libraries:

```
~/ALCDA2/x64/App1$ gdb -c App1.shared.core.275 -se App1.shared
GNU gdb (Debian 8.2.1-2+b3) 8.2.1
Copyright (C) 2018 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
```

```

Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<http://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from App1.shared...(no debugging symbols found)...done.
[New LWP 275]
[New LWP 276]
[New LWP 277]
[New LWP 278]
[New LWP 279]
[New LWP 280]
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Core was generated by `./App1.shared'.
#0 0x00007f1ae471e720 in __GI__nanosleep (requested_time=requested_time@entry=0x7ffc74957a90,
remaining=remaining@entry=0x7ffc74957a90) at ../sysdeps/unix/sysv/linux/nanosleep.c:28
28     .../sysdeps/unix/sysv/linux/nanosleep.c: No such file or directory.
[Current thread is 1 (Thread 0x7f1ae4655740 (LWP 275))]
```

(gdb) info sharedlibrary				
From	To	Syms	Read	Shared Object Library
0x00007f1ae481f5b0	0x00007f1ae482d641	Yes		/lib/x86_64-linux-gnu/libpthread.so.0
0x00007f1ae467a320	0x00007f1ae47c039b	Yes		/lib/x86_64-linux-gnu/libc.so.6
0x00007f1ae4848090	0x00007f1ae4865b20	Yes		/lib64/ld-linux-x86-64.so.2

16. Disassemble *bar_one* function and follow the indirect *sleep* function call:

```

(gdb) disassemble bar_one
Dump of assembler code for function bar_one:
0x0000557e17348145 <+0>:    push    %rbp
0x0000557e17348146 <+1>:    mov     %rsp,%rbp
0x0000557e17348149 <+4>:    mov     $0xffffffff,%edi
0x0000557e1734814e <+9>:    callq   0x557e17348040 <sleep@plt>
0x0000557e17348153 <+14>:   nop
0x0000557e17348154 <+15>:   pop    %rbp
0x0000557e17348155 <+16>:   retq
```

End of assembler dump.

```

(gdb) disassemble 0x557e17348040
Dump of assembler code for function sleep@plt:
0x0000557e17348040 <+0>:    jmpq   *0x2fda(%rip)          # 0x557e1734b020 <sleep@got.plt>
0x0000557e17348046 <+6>:    pushq   $0x1
0x0000557e1734804b <+11>:   jmpq   0x557e17348020
End of assembler dump.
```

17. Dump the annotated value as a memory address interpreting its contents as a symbol:

```

(gdb) p/x 0x0000557e17348046+0x2fda
$1 = 0x557e1734b020

(gdb) x/a 0x557e1734b020
0x557e1734b020 <sleep@got.plt>: 0x7f1ae471e5f0 <__sleep>
```

Note: Since GDB gets shared library images from your analysis system which do not correspond to shared libraries from the crash system, most likely you get some random symbolic information (and also an invalid backtrace from the **bt** command):

```
(gdb) x/a 0x557e1734b020  
0x557e1734b020 <sleep@got.plt>: 0x7f1ae471e5f0 <__getpwnam_r+288>
```

Note: You need the original shared library images and debug symbol files from the problem system. To get the right results for this exercise, you can recreate the *App1.shared* core dump (see *main.c* for build instructions if necessary).

18. *App1.shared.pmap.275* also shows library memory regions:

```
(gdb) q  
~/ALCDA2/x64/App1$ cat App1.shared.pmap.275  
275: ./App1.shared  
0000557e17347000      4K r---- App1.shared  
0000557e17348000      4K r-x-- App1.shared  
0000557e17349000      4K r---- App1.shared  
0000557e1734a000      4K r---- App1.shared  
0000557e1734b000      4K rw--- App1.shared  
0000557e179ca000     132K rw--- [ anon ]  
00007f1ae1e50000      4K ----- [ anon ]  
00007f1ae1e51000     8192K rw--- [ anon ]  
00007f1ae2651000      4K ----- [ anon ]  
00007f1ae2652000     8192K rw--- [ anon ]  
00007f1ae2e52000      4K ----- [ anon ]  
00007f1ae2e53000     8192K rw--- [ anon ]  
00007f1ae3653000      4K ----- [ anon ]  
00007f1ae3654000     8192K rw--- [ anon ]  
00007f1ae3e54000      4K ----- [ anon ]  
00007f1ae3e55000     8204K rw--- [ anon ]  
00007f1ae4658000     136K r---- libc-2.28.so  
00007f1ae467a000     1312K r-x-- libc-2.28.so  
00007f1ae47c2000     304K r---- libc-2.28.so  
00007f1ae480e000      4K ----- libc-2.28.so  
00007f1ae480f000     16K r---- libc-2.28.so  
00007f1ae4813000      8K rw--- libc-2.28.so  
00007f1ae4815000     16K rw--- [ anon ]  
00007f1ae4819000     24K r---- libpthread-2.28.so  
00007f1ae481f000     60K r-x-- libpthread-2.28.so  
00007f1ae482e000     24K r---- libpthread-2.28.so  
00007f1ae4834000      4K r---- libpthread-2.28.so  
00007f1ae4835000      4K rw--- libpthread-2.28.so  
00007f1ae4836000     24K rw--- [ anon ]  
00007f1ae4847000      4K r---- ld-2.28.so  
00007f1ae4848000     120K r-x-- ld-2.28.so  
00007f1ae4866000     32K r---- ld-2.28.so  
00007f1ae486e000      4K r---- ld-2.28.so  
00007f1ae486f000      4K rw--- ld-2.28.so  
00007f1ae4870000      4K rw--- [ anon ]  
00007ffc74939000     132K rw--- [ stack ]  
00007ffc749ac000      16K r---- [ anon ]  
00007ffc749b0000      4K r-x-- [ anon ]  
total                  43400K
```

Exercise A1 (A64, GDB)

Goal: Learn how to list stack traces, disassemble functions, check their correctness, dump data, get environment.

Patterns: Manual Dump (Process); Stack Trace; Stack Trace Collection; Annotated Disassembly; Paratext; Not My Version; Environment Hint.

1. Load a core dump *App1.core.21174* and *App1* executable from the A64/App1 directory:

```
~/ALCDA2/A64/App1$ gdb -c App1.core.21174 -se App1
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "aarch64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
  <http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from App1...
(No debugging symbols found in App1)

warning: Can't open file /home/opc/ALCDA2/App1/App1 during file-backed mapping note processing
[New LWP 21175]
[New LWP 21176]
[New LWP 21177]
[New LWP 21178]
[New LWP 21179]
[New LWP 21174]
Core was generated by `./App1'.
#0 0x000000000040c9b4 in nanosleep ()
[Current thread is 1 (LWP 21175)]
```

2. Set logging to a file in case of lengthy output from some commands and set color highlighting off:

```
(gdb) set logging file App1.log
(gdb) set logging enabled on
Copying output to App1.log.
Copying debug output to App1.log.

(gdb) set style enabled off
```

3. List all threads:

```
(gdb) info threads
  Id  Target Id      Frame
* 1    LWP 21175    0x000000000040c9b4 in nanosleep ()
  2    LWP 21176    0x000000000040c9b4 in nanosleep ()
  3    LWP 21177    0x000000000040c9b4 in nanosleep ()
  4    LWP 21178    0x000000000040c9b4 in nanosleep ()
  5    LWP 21179    0x000000000040c9b4 in nanosleep ()
```

```
6      LWP 21174          0x000000000040c9b4 in nanosleep ()
```

4. Get the current thread stack trace:

```
(gdb) bt
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x00000000004031f8 in bar_one ()
#3 0x000000000040320c in foo_one ()
#4 0x0000000000403224 in thread_one ()
#5 0x0000000000404c34 in start_thread ()
#6 0x0000000000429b60 in thread_start ()
```

5. Get all thread stack traces:

```
(gdb) thread apply all bt
Thread 6 (LWP 21174):
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x00000000004033e0 in main ()

Thread 5 (LWP 21179):
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x0000000000403318 in bar_five ()
#3 0x000000000040332c in foo_five ()
#4 0x0000000000403344 in thread_five ()
#5 0x0000000000404c34 in start_thread ()
#6 0x0000000000429b60 in thread_start ()

Thread 4 (LWP 21178):
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x00000000004032d0 in bar_four ()
#3 0x00000000004032e4 in foo_four ()
#4 0x00000000004032fc in thread_four ()
#5 0x0000000000404c34 in start_thread ()
#6 0x0000000000429b60 in thread_start ()

Thread 3 (LWP 21177):
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x0000000000403288 in bar_three ()
#3 0x000000000040329c in foo_three ()
#4 0x00000000004032b4 in thread_three ()
#5 0x0000000000404c34 in start_thread ()
#6 0x0000000000429b60 in thread_start ()

Thread 2 (LWP 21176):
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x0000000000403240 in bar_two ()
#3 0x0000000000403254 in foo_two ()
#4 0x000000000040326c in thread_two ()
#5 0x0000000000404c34 in start_thread ()
#6 0x0000000000429b60 in thread_start ()
```

```
Thread 1 (LWP 21175):
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x00000000004031f8 in bar_one ()
#3 0x000000000040320c in foo_one ()
#4 0x0000000000403224 in thread_one ()
#5 0x0000000000404c34 in start_thread ()
#6 0x0000000000429b60 in thread_start ()
```

6. Switch to thread #2 and get its stack trace:

```
(gdb) thread 2
[Switching to thread 2 (LWP 21176)]
#0 0x000000000040c9b4 in nanosleep ()
```

```
(gdb) bt
#0 0x000000000040c9b4 in nanosleep ()
#1 0x0000000000424cb4 in sleep ()
#2 0x0000000000403240 in bar_two ()
#3 0x0000000000403254 in foo_two ()
#4 0x000000000040326c in thread_two ()
#5 0x0000000000404c34 in start_thread ()
#6 0x0000000000429b60 in thread_start ()
```

```
(gdb) info threads
Id      Target Id        Frame
 1      LWP 21175       0x000000000040c9b4 in nanosleep ()
* 2      LWP 21176       0x000000000040c9b4 in nanosleep ()
 3      LWP 21177       0x000000000040c9b4 in nanosleep ()
 4      LWP 21178       0x000000000040c9b4 in nanosleep ()
 5      LWP 21179       0x000000000040c9b4 in nanosleep ()
 6      LWP 21174       0x000000000040c9b4 in nanosleep ()
```

7. Check that *bar_two* called the *sleep* function by comparing the return address on the call stack from the disassembly output:

```
(gdb) disassemble bar_two
Dump of assembler code for function bar_two:
0x0000000000403230 <+0>:    stp    x29, x30, [sp, #-16]!
0x0000000000403234 <+4>:    mov    x29, sp
0x0000000000403238 <+8>:    mov    w0, #0xffffffff          // #-1
0x000000000040323c <+12>:   bl     0x424ba4 <sleep>
0x0000000000403240 <+16>:   ldp    x29, x30, [sp], #16
0x0000000000403244 <+20>:   ret
End of assembler dump.
```

We see that the address in the stack trace for the *bar_two* function is the address to return to after calling the *sleep* function.

8. Get *App1* data section from the output of pmap (*App1.pmap.21174*):

```
(gdb) ^Z
[1]+ Stopped                  gdb -c App1.core.21174 -se App1
```

```
~/ALCDA2/A64/App1$ cat App1.pmap.21174
21174: ./App1
0000000000400000    768K r-x-- App1
00000000004c0000    128K rw--- App1
0000000001fa0000    256K rw--- [ anon ]
```

```

0000ffffcab40000    64K ----- [ anon ]
0000ffffcab50000   8192K rw--- [ anon ]
0000ffffccb350000    64K ----- [ anon ]
0000ffffccb360000   8192K rw--- [ anon ]
0000ffffccb60000    64K ----- [ anon ]
0000ffffccb70000   8192K rw--- [ anon ]
0000ffffccc370000    64K ----- [ anon ]
0000ffffccc380000   8192K rw--- [ anon ]
0000ffffccb80000    64K ----- [ anon ]
0000ffffccb90000   8192K rw--- [ anon ]
0000ffffcd390000    64K r---- [ anon ]
0000ffffcd3a0000    64K r-x-- [ anon ]
0000fffffd3090000   192K rw--- [ stack ]
total                42752K

```

```

~/ALCDA2/A64/App1$ fg
gdb -c App1.core.21174 -se App1

```

(gdb)

9. Compare with the section information in the core dump:

```

(gdb) p/x 0x0000000004c0000+128*1024
$1 = 0x4e0000

```

```

(gdb) maintenance info sections
Exec file: `/home/ubuntu/ALCDA2/A64/App1/App1', file type elf64-littleaarch64.
[0] 0x00400190->0x004001b0 at 0x000000190: .note.ABI-tag ALLOC LOAD READONLY DATA HAS_CONTENTS
[1] 0x004001b0->0x004001d4 at 0x0000001b0: .note.gnu.build-id ALLOC LOAD READONLY DATA HAS_CONTENTS
[2] 0x004001d8->0x00400250 at 0x0000001d8: .rela.plt ALLOC LOAD READONLY DATA HAS_CONTENTS
[3] 0x00400250->0x00400264 at 0x000000250: .init ALLOC LOAD READONLY CODE HAS_CONTENTS
[4] 0x00400270->0x004002c0 at 0x000000270: .plt ALLOC LOAD READONLY CODE HAS_CONTENTS
[5] 0x004002c0->0x00487098 at 0x0000002c0: .text ALLOC LOAD READONLY CODE HAS_CONTENTS
[6] 0x00487098->0x00488d68 at 0x00087098: __libc_freeres_fn ALLOC LOAD READONLY CODE HAS_CONTENTS
[7] 0x00488d68->0x004891b8 at 0x00088d68: __libc_thread_freeres_fn ALLOC LOAD READONLY CODE HAS_CONTENTS
HAS_CONTENTS
[8] 0x004891b8->0x004891c8 at 0x000891b8: .fini ALLOC LOAD READONLY CODE HAS_CONTENTS
[9] 0x004891d0->0x004a16ad at 0x000891d0: .rodata ALLOC LOAD READONLY DATA HAS_CONTENTS
[10] 0x004a16ad->0x004a16ae at 0x000a16ad: .stapsdt.base ALLOC LOAD READONLY DATA HAS_CONTENTS
[11] 0x004a16b0->0x004a1de8 at 0x000a16b0: __libc_IO_vtables ALLOC LOAD READONLY DATA HAS_CONTENTS
[12] 0x004a1de8->0x004a1e50 at 0x000a1de8: __libc_subfreeres ALLOC LOAD READONLY DATA HAS_CONTENTS
[13] 0x004a1e50->0x004a1e58 at 0x000a1e50: __libc_atexit ALLOC LOAD READONLY DATA HAS_CONTENTS
[14] 0x004a1e58->0x004a1e68 at 0x000a1e58: __libc_thread_subfreeres ALLOC LOAD READONLY DATA HAS_CONTENTS
HAS_CONTENTS
[15] 0x004a1e68->0x004b047c at 0x000a1e68: .eh_frame ALLOC LOAD READONLY DATA HAS_CONTENTS
[16] 0x004b047c->0x004b0639 at 0x000b047c: .gcc_except_table ALLOC LOAD READONLY DATA HAS_CONTENTS
[17] 0x004cfb20->0x004cfb48 at 0x000bf20: .tdata ALLOC LOAD DATA HAS_CONTENTS
[18] 0x004cfb48->0x004cfb98 at 0x000bf24: .tbss ALLOC
[19] 0x004cfb48->0x004cfb50 at 0x000bf28: .init_array ALLOC LOAD DATA HAS_CONTENTS
[20] 0x004cfb50->0x004cfb60 at 0x000bf2c: .fini_array ALLOC LOAD DATA HAS_CONTENTS
[21] 0x004cfb60->0x004cfb68 at 0x000bf30: .jcr ALLOC LOAD DATA HAS_CONTENTS
[22] 0x004cfb68->0x004cff24 at 0x000bf38: .data.rel.ro ALLOC LOAD DATA HAS_CONTENTS
[23] 0x004cff28->0x004cffe8 at 0x000bf48: .got ALLOC LOAD DATA HAS_CONTENTS
[24] 0x004cffe8->0x004d0028 at 0x000bf58: .got.plt ALLOC LOAD DATA HAS_CONTENTS
[25] 0x004d0030->0x004d1580 at 0x000c0030: .data ALLOC LOAD DATA HAS_CONTENTS
[26] 0x004d1580->0x004d8050 at 0x000c1580: .bss ALLOC
[27] 0x004d8050->0x004d8088 at 0x000c1580: __libc_freeres_ptrs ALLOC
[28] 0x00000000->0x00000031 at 0x000c1580: .comment READONLY HAS_CONTENTS
[29] 0x00000000->0x00001cb0 at 0x000c15b4: .note.stapsdt READONLY HAS_CONTENTS
Core file: `/home/ubuntu/ALCDA2/A64/App1/App1.core.21174', file type elf64-littleaarch64.
[0] 0x00000000->0x00001c94 at 0x0000003c0: note0 READONLY HAS_CONTENTS
[1] 0x00000000->0x000000110 at 0x0000004e0: .reg/21175 HAS_CONTENTS
[2] 0x00000000->0x000000110 at 0x0000004e0: .reg HAS_CONTENTS

```

```

[3] 0x00000000->0x00000210 at 0x0000060c: .reg2/21175 HAS_CONTENTS
[4] 0x00000000->0x00000210 at 0x0000060c: .reg2 HAS_CONTENTS
[5] 0x00000000->0x00000080 at 0x00000830: .note.linuxcore.siginfo/21175 HAS_CONTENTS
[6] 0x00000000->0x00000080 at 0x00000830: .note.linuxcore.siginfo HAS_CONTENTS
[7] 0x00000000->0x00000110 at 0x00000934: .reg/21176 HAS_CONTENTS
[8] 0x00000000->0x00000210 at 0x00000a60: .reg2/21176 HAS_CONTENTS
[9] 0x00000000->0x00000080 at 0x00000c84: .note.linuxcore.siginfo/21176 HAS_CONTENTS
[10] 0x00000000->0x00000110 at 0x00000d88: .reg/21177 HAS_CONTENTS
[11] 0x00000000->0x00000210 at 0x00000eb4: .reg2/21177 HAS_CONTENTS
[12] 0x00000000->0x00000080 at 0x000010d8: .note.linuxcore.siginfo/21177 HAS_CONTENTS
[13] 0x00000000->0x00000110 at 0x000011dc: .reg/21178 HAS_CONTENTS
[14] 0x00000000->0x00000210 at 0x00001308: .reg2/21178 HAS_CONTENTS
[15] 0x00000000->0x00000080 at 0x0000152c: .note.linuxcore.siginfo/21178 HAS_CONTENTS
[16] 0x00000000->0x00000110 at 0x00001630: .reg/21179 HAS_CONTENTS
[17] 0x00000000->0x00000210 at 0x0000175c: .reg2/21179 HAS_CONTENTS
--Type <RET> for more, q to quit, c to continue without paging--
[18] 0x00000000->0x00000080 at 0x00001980: .note.linuxcore.siginfo/21179 HAS_CONTENTS
[19] 0x00000000->0x00000110 at 0x00001a84: .reg/21174 HAS_CONTENTS
[20] 0x00000000->0x00000210 at 0x00001bb0: .reg2/21174 HAS_CONTENTS
[21] 0x00000000->0x00000080 at 0x00001dd4: .note.linuxcore.siginfo/21174 HAS_CONTENTS
[22] 0x00000000->0x00000160 at 0x00001e68: .auxv HAS_CONTENTS
[23] 0x00000000->0x00000076 at 0x00001fdc: .note.linuxcore.file/21174 HAS_CONTENTS
[24] 0x00000000->0x00000076 at 0x00001fdc: .note.linuxcore.file HAS_CONTENTS
[25] 0x00400000->0x004c0000 at 0x00002054: load1 ALLOC LOAD READONLY CODE HAS_CONTENTS
[26] 0x004c0000->0x004e0000 at 0x000c2054: load2 ALLOC LOAD HAS_CONTENTS
[27] 0x01fa0000->0x01fe0000 at 0x000e2054: load3 ALLOC LOAD HAS_CONTENTS
[28] 0xffffcab40000->0xffffcab50000 at 0x00122054: load4 ALLOC LOAD READONLY HAS_CONTENTS
[29] 0xffffcab50000->0xffffccb350000 at 0x00132054: load5 ALLOC LOAD HAS_CONTENTS
[30] 0xffffccb350000->0xffffccb360000 at 0x00932054: load6 ALLOC LOAD READONLY HAS_CONTENTS
[31] 0xffffccb360000->0xffffccb60000 at 0x00942054: load7 ALLOC LOAD HAS_CONTENTS
[32] 0xffffccb60000->0xffffccb70000 at 0x01142054: load8 ALLOC LOAD READONLY HAS_CONTENTS
[33] 0xffffccb70000->0xffffccc370000 at 0x01152054: load9 ALLOC LOAD HAS_CONTENTS
[34] 0xffffccc370000->0xffffccc380000 at 0x01952054: load10 ALLOC LOAD READONLY HAS_CONTENTS
[35] 0xffffccc380000->0xffffccb80000 at 0x01962054: load11 ALLOC LOAD HAS_CONTENTS
[36] 0xffffccb80000->0xffffccb90000 at 0x02162054: load12 ALLOC LOAD READONLY HAS_CONTENTS
[37] 0xffffccb90000->0xffffccd390000 at 0x02172054: load13 ALLOC LOAD HAS_CONTENTS
[38] 0xffffccd3a0000->0xffffccd3b0000 at 0x02972054: load14 ALLOC LOAD READONLY CODE HAS_CONTENTS
[39] 0xfffffd3090000->0xfffffd30c0000 at 0x02982054: load15 ALLOC LOAD HAS_CONTENTS

```

10. Dump the first 600 addresses from the **.data** section with possible symbolic information:

```

(gdb) x/600a 0x004d0030
0x4d0030: 0x0 0x4d0038 <stack_cache>
0x4d0040 <stack_cache+8>: 0x4d0038 <stack_cache> 0x6
0x4d0050 <stack_used>: 0xffffccb34f140 0xffffcccd38f140
0x4d0060 <__sched_fifo_max_prio>: 0xffffffffffffffff 0x890
0x4d0070 <__exit_funcs>: 0x4d5eb0 <initial> 0x486b88 <_gcc_personality_v0>
0x4d0080 <_IO_list_all>: 0x4d0088 <_IO_2_1_stderr_> 0xfbdb2086
0x4d0090 <_IO_2_1_stderr_+8>: 0x0 0x0
0x4d00a0 <_IO_2_1_stderr_+24>: 0x0 0x0
0x4d00b0 <_IO_2_1_stderr_+40>: 0x0 0x0
0x4d00c0 <_IO_2_1_stderr_+56>: 0x0 0x0
0x4d00d0 <_IO_2_1_stderr_+72>: 0x0 0x0
0x4d00e0 <_IO_2_1_stderr_+88>: 0x0 0x0
0x4d00f0 <_IO_2_1_stderr_+104>: 0x4d02b0 <_IO_2_1_stdout_> 0x2
0x4d0100 <_IO_2_1_stderr_+120>: 0xfffffffffffffff 0x0
0x4d0110 <_IO_2_1_stderr_+136>: 0x4d6428 <_IO_stdio_2_lock_> 0xfffffffffffffff
0x4d0120 <_IO_2_1_stderr_+152>: 0x0 0x4d0168 <_IO_wide_data_2>
0x4d0130 <_IO_2_1_stderr_+168>: 0x0 0x0
0x4d0140 <_IO_2_1_stderr_+184>: 0x0 0x0
0x4d0150 <_IO_2_1_stderr_+200>: 0x0 0x0
0x4d0160 <_IO_2_1_stderr_+216>: 0x4a1950 <_IO_file_jumps> 0x0
0x4d0170 <_IO_wide_data_2+8>: 0x0 0x0
0x4d0180 <_IO_wide_data_2+24>: 0x0 0x0

```

```

0x4d0190 <_IO_wide_data_2+40>: 0x0      0x0
0x4d01a0 <_IO_wide_data_2+56>: 0x0      0x0
0x4d01b0 <_IO_wide_data_2+72>: 0x0      0x0
0x4d01c0 <_IO_wide_data_2+88>: 0x0      0x0
0x4d01d0 <_IO_wide_data_2+104>: 0x0      0x0
0x4d01e0 <_IO_wide_data_2+120>: 0x0      0x0
0x4d01f0 <_IO_wide_data_2+136>: 0x0      0x0
0x4d0200 <_IO_wide_data_2+152>: 0x0      0x0
0x4d0210 <_IO_wide_data_2+168>: 0x0      0x0
0x4d0220 <_IO_wide_data_2+184>: 0x0      0x0
0x4d0230 <_IO_wide_data_2+200>: 0x0      0x0
0x4d0240 <_IO_wide_data_2+216>: 0x0      0x0
0x4d0250 <_IO_wide_data_2+232>: 0x0      0x0
0x4d0260 <_IO_wide_data_2+248>: 0x0      0x0
0x4d0270 <_IO_wide_data_2+264>: 0x0      0x0
0x4d0280 <_IO_wide_data_2+280>: 0x0      0x0
0x4d0290 <_IO_wide_data_2+296>: 0x0      0x0
0x4d02a0 <_IO_wide_data_2+312>: 0x0      0x4a1800 <_IO_wfile_jumps>
0x4d02b0 <_IO_2_1_stdout_>:    0xfbada2084      0x0
0x4d02c0 <_IO_2_1_stdout_+16>: 0x0      0x0
0x4d02d0 <_IO_2_1_stdout_+32>: 0x0      0x0
0x4d02e0 <_IO_2_1_stdout_+48>: 0x0      0x0
0x4d02f0 <_IO_2_1_stdout_+64>: 0x0      0x0
0x4d0300 <_IO_2_1_stdout_+80>: 0x0      0x0
0x4d0310 <_IO_2_1_stdout_+96>: 0x0      0x4d04d8 <_IO_2_1_stdin_>
0x4d0320 <_IO_2_1_stdout_+112>: 0x1      0xffffffffffffffffffff
0x4d0330 <_IO_2_1_stdout_+128>: 0x0      0x4d6438 <_IO_stdfile_1_lock>
0x4d0340 <_IO_2_1_stdout_+144>: 0xffffffffffff      0x0
--Type <RET> for more, q to quit, c to continue without paging--
0x4d0350 <_IO_2_1_stdout_+160>: 0x4d0390 <_IO_wide_data_1>      0x0
0x4d0360 <_IO_2_1_stdout_+176>: 0x0      0x0
0x4d0370 <_IO_2_1_stdout_+192>: 0x0      0x0
0x4d0380 <_IO_2_1_stdout_+208>: 0x0      0x4a1950 <_IO_file_jumps>
0x4d0390 <_IO_wide_data_1>: 0x0      0x0
0x4d03a0 <_IO_wide_data_1+16>: 0x0      0x0
0x4d03b0 <_IO_wide_data_1+32>: 0x0      0x0
0x4d03c0 <_IO_wide_data_1+48>: 0x0      0x0
0x4d03d0 <_IO_wide_data_1+64>: 0x0      0x0
0x4d03e0 <_IO_wide_data_1+80>: 0x0      0x0
0x4d03f0 <_IO_wide_data_1+96>: 0x0      0x0
0x4d0400 <_IO_wide_data_1+112>: 0x0      0x0
0x4d0410 <_IO_wide_data_1+128>: 0x0      0x0
0x4d0420 <_IO_wide_data_1+144>: 0x0      0x0
0x4d0430 <_IO_wide_data_1+160>: 0x0      0x0
0x4d0440 <_IO_wide_data_1+176>: 0x0      0x0
0x4d0450 <_IO_wide_data_1+192>: 0x0      0x0
0x4d0460 <_IO_wide_data_1+208>: 0x0      0x0
0x4d0470 <_IO_wide_data_1+224>: 0x0      0x0
0x4d0480 <_IO_wide_data_1+240>: 0x0      0x0
0x4d0490 <_IO_wide_data_1+256>: 0x0      0x0
0x4d04a0 <_IO_wide_data_1+272>: 0x0      0x0
0x4d04b0 <_IO_wide_data_1+288>: 0x0      0x0
0x4d04c0 <_IO_wide_data_1+304>: 0x0      0x0
0x4d04d0 <_IO_wide_data_1+320>: 0x4a1800 <_IO_wfile_jumps>      0xfbada2088
0x4d04e0 <_IO_2_1_stdin_+8>: 0x0      0x0
0x4d04f0 <_IO_2_1_stdin_+24>: 0x0      0x0
0x4d0500 <_IO_2_1_stdin_+40>: 0x0      0x0
0x4d0510 <_IO_2_1_stdin_+56>: 0x0      0x0
0x4d0520 <_IO_2_1_stdin_+72>: 0x0      0x0
0x4d0530 <_IO_2_1_stdin_+88>: 0x0      0x0

```

```

0x4d0540 <_IO_2_1_stdin_+104>: 0x0      0x0
0x4d0550 <_IO_2_1_stdin_+120>: 0xfffffffffffffff      0x0
0x4d0560 <_IO_2_1_stdin_+136>: 0x4d6448 <_IO_stdfile_0_lock>  0xfffffffffffffff
0x4d0570 <_IO_2_1_stdin_+152>: 0x0      0x4d05b8 <_IO_wide_data_0>
0x4d0580 <_IO_2_1_stdin_+168>: 0x0      0x0
0x4d0590 <_IO_2_1_stdin_+184>: 0x0      0x0
0x4d05a0 <_IO_2_1_stdin_+200>: 0x0      0x0
0x4d05b0 <_IO_2_1_stdin_+216>: 0x4a1950 <_IO_file_jumps>      0x0
0x4d05c0 <_IO_wide_data_0+8>: 0x0      0x0
0x4d05d0 <_IO_wide_data_0+24>: 0x0      0x0
0x4d05e0 <_IO_wide_data_0+40>: 0x0      0x0
0x4d05f0 <_IO_wide_data_0+56>: 0x0      0x0
0x4d0600 <_IO_wide_data_0+72>: 0x0      0x0
0x4d0610 <_IO_wide_data_0+88>: 0x0      0x0
0x4d0620 <_IO_wide_data_0+104>: 0x0      0x0
0x4d0630 <_IO_wide_data_0+120>: 0x0      0x0
0x4d0640 <_IO_wide_data_0+136>: 0x0      0x0
0x4d0650 <_IO_wide_data_0+152>: 0x0      0x0
0x4d0660 <_IO_wide_data_0+168>: 0x0      0x0
--Type <RET> for more, q to quit, c to continue without paging--
0x4d0670 <_IO_wide_data_0+184>: 0x0      0x0
0x4d0680 <_IO_wide_data_0+200>: 0x0      0x0
0x4d0690 <_IO_wide_data_0+216>: 0x0      0x0
0x4d06a0 <_IO_wide_data_0+232>: 0x0      0x0
0x4d06b0 <_IO_wide_data_0+248>: 0x0      0x0
0x4d06c0 <_IO_wide_data_0+264>: 0x0      0x0
0x4d06d0 <_IO_wide_data_0+280>: 0x0      0x0
0x4d06e0 <_IO_wide_data_0+296>: 0x0      0x0
0x4d06f0 <_IO_wide_data_0+312>: 0x0      0x4a1800 <_IO_wfile_jumps>
0x4d0700 <stderr>:    0x4d0088 <_IO_2_1_stderr_>      0x4d02b0 <_IO_2_1_stdout_>
0x4d0710 <stdin>:    0x4d04d8 <_IO_2_1_stdin_>      0x20000
0x4d0720 <mp_+8>:    0x20000 0x20000
0x4d0730 <mp_+24>:   0x8     0x0
0x4d0740 <mp_+40>:   0x10000000000000 0x0
0x4d0750 <mp_+56>:   0x0     0x0
0x4d0760 <mp_+72>:   0x1fa0f88      0x40
0x4d0770 <mp_+88>:   0x408     0x7
0x4d0780 <mp_+104>:  0x0     0x0
0x4d0790 <main_arena+8>: 0x0     0x0
0x4d07a0 <main_arena+24>: 0x0     0x0
0x4d07b0 <main_arena+40>: 0x0     0x0
0x4d07c0 <main_arena+56>: 0x0     0x0
0x4d07d0 <main_arena+72>: 0x0     0x0
0x4d07e0 <main_arena+88>: 0x0     0x1fa28a0
0x4d07f0 <main_arena+104>: 0x0     0x4d07e8 <main_arena+96>
0x4d0800 <main_arena+120>: 0x4d07e8 <main_arena+96>      0x4d07f8 <main_arena+112>
0x4d0810 <main_arena+136>: 0x4d07f8 <main_arena+112>      0x4d0808 <main_arena+128>
0x4d0820 <main_arena+152>: 0x4d0808 <main_arena+128>      0x4d0818 <main_arena+144>
0x4d0830 <main_arena+168>: 0x4d0818 <main_arena+144>      0x4d0828 <main_arena+160>
0x4d0840 <main_arena+184>: 0x4d0828 <main_arena+160>      0x4d0838 <main_arena+176>
0x4d0850 <main_arena+200>: 0x4d0838 <main_arena+176>      0x4d0848 <main_arena+192>
0x4d0860 <main_arena+216>: 0x4d0848 <main_arena+192>      0x4d0858 <main_arena+208>
0x4d0870 <main_arena+232>: 0x4d0858 <main_arena+208>      0x4d0868 <main_arena+224>
0x4d0880 <main_arena+248>: 0x4d0868 <main_arena+224>      0x4d0878 <main_arena+240>
0x4d0890 <main_arena+264>: 0x4d0878 <main_arena+240>      0x4d0888 <main_arena+256>
0x4d08a0 <main_arena+280>: 0x4d0888 <main_arena+256>      0x4d0898 <main_arena+272>
0x4d08b0 <main_arena+296>: 0x4d0898 <main_arena+272>      0x4d08a8 <main_arena+288>
0x4d08c0 <main_arena+312>: 0x4d08a8 <main_arena+288>      0x4d08b8 <main_arena+304>
0x4d08d0 <main_arena+328>: 0x4d08b8 <main_arena+304>      0x4d08c8 <main_arena+320>
0x4d08e0 <main_arena+344>: 0x4d08c8 <main_arena+320>      0x4d08d8 <main_arena+336>

```

```

0x4d08f0 <main_arena+360>: 0x4d08d8 <main_arena+336> 0x4d08e8 <main_arena+352>
0x4d0900 <main_arena+376>: 0x4d08e8 <main_arena+352> 0x4d08f8 <main_arena+368>
0x4d0910 <main_arena+392>: 0x4d08f8 <main_arena+368> 0x4d0908 <main_arena+384>
0x4d0920 <main_arena+408>: 0x4d0908 <main_arena+384> 0x4d0918 <main_arena+400>
0x4d0930 <main_arena+424>: 0x4d0918 <main_arena+400> 0x4d0928 <main_arena+416>
0x4d0940 <main_arena+440>: 0x4d0928 <main_arena+416> 0x4d0938 <main_arena+432>
0x4d0950 <main_arena+456>: 0x4d0938 <main_arena+432> 0x4d0948 <main_arena+448>
0x4d0960 <main_arena+472>: 0x4d0948 <main_arena+448> 0x4d0958 <main_arena+464>
0x4d0970 <main_arena+488>: 0x4d0958 <main_arena+464> 0x4d0968 <main_arena+480>
0x4d0980 <main_arena+504>: 0x4d0968 <main_arena+480> 0x4d0978 <main_arena+496>
--Type <RET> for more, q to quit, c to continue without paging--
0x4d0990 <main_arena+520>: 0x4d0978 <main_arena+496> 0x4d0988 <main_arena+512>
0x4d09a0 <main_arena+536>: 0x4d0988 <main_arena+512> 0x4d0998 <main_arena+528>
0x4d09b0 <main_arena+552>: 0x4d0998 <main_arena+528> 0x4d09a8 <main_arena+544>
0x4d09c0 <main_arena+568>: 0x4d09a8 <main_arena+544> 0x4d09b8 <main_arena+560>
0x4d09d0 <main_arena+584>: 0x4d09b8 <main_arena+560> 0x4d09c8 <main_arena+576>
0x4d09e0 <main_arena+600>: 0x4d09c8 <main_arena+576> 0x4d09d8 <main_arena+592>
0x4d09f0 <main_arena+616>: 0x4d09d8 <main_arena+592> 0x4d09e8 <main_arena+608>
0x4d0a00 <main_arena+632>: 0x4d09e8 <main_arena+608> 0x4d09f8 <main_arena+624>
0x4d0a10 <main_arena+648>: 0x4d09f8 <main_arena+624> 0x4d0a08 <main_arena+640>
0x4d0a20 <main_arena+664>: 0x4d0a08 <main_arena+640> 0x4d0a18 <main_arena+656>
0x4d0a30 <main_arena+680>: 0x4d0a18 <main_arena+656> 0x4d0a28 <main_arena+672>
0x4d0a40 <main_arena+696>: 0x4d0a28 <main_arena+672> 0x4d0a38 <main_arena+688>
0x4d0a50 <main_arena+712>: 0x4d0a38 <main_arena+688> 0x4d0a48 <main_arena+704>
0x4d0a60 <main_arena+728>: 0x4d0a48 <main_arena+704> 0x4d0a58 <main_arena+720>
0x4d0a70 <main_arena+744>: 0x4d0a58 <main_arena+720> 0x4d0a68 <main_arena+736>
0x4d0a80 <main_arena+760>: 0x4d0a68 <main_arena+736> 0x4d0a78 <main_arena+752>
0x4d0a90 <main_arena+776>: 0x4d0a78 <main_arena+752> 0x4d0a88 <main_arena+768>
0x4d0aa0 <main_arena+792>: 0x4d0a88 <main_arena+768> 0x4d0a98 <main_arena+784>
0x4d0ab0 <main_arena+808>: 0x4d0a98 <main_arena+784> 0x4d0aa8 <main_arena+800>
0x4d0ac0 <main_arena+824>: 0x4d0aa8 <main_arena+800> 0x4d0ab8 <main_arena+816>
0x4d0ad0 <main_arena+840>: 0x4d0ab8 <main_arena+816> 0x4d0ac8 <main_arena+832>
0x4d0ae0 <main_arena+856>: 0x4d0ac8 <main_arena+832> 0x4d0ad8 <main_arena+848>
0x4d0af0 <main_arena+872>: 0x4d0ad8 <main_arena+848> 0x4d0ae8 <main_arena+864>
0x4d0b00 <main_arena+888>: 0x4d0ae8 <main_arena+864> 0x4d0af8 <main_arena+880>
0x4d0b10 <main_arena+904>: 0x4d0af8 <main_arena+880> 0x4d0b08 <main_arena+896>
0x4d0b20 <main_arena+920>: 0x4d0b08 <main_arena+896> 0x4d0b18 <main_arena+912>
0x4d0b30 <main_arena+936>: 0x4d0b18 <main_arena+912> 0x4d0b28 <main_arena+928>
0x4d0b40 <main_arena+952>: 0x4d0b28 <main_arena+928> 0x4d0b38 <main_arena+944>
0x4d0b50 <main_arena+968>: 0x4d0b38 <main_arena+944> 0x4d0b48 <main_arena+960>
0x4d0b60 <main_arena+984>: 0x4d0b48 <main_arena+960> 0x4d0b58 <main_arena+976>
0x4d0b70 <main_arena+1000>: 0x4d0b58 <main_arena+976> 0x4d0b68 <main_arena+992>
0x4d0b80 <main_arena+1016>: 0x4d0b68 <main_arena+992> 0x4d0b78 <main_arena+1008>
0x4d0b90 <main_arena+1032>: 0x4d0b78 <main_arena+1008> 0x4d0b88 <main_arena+1024>
0x4d0ba0 <main_arena+1048>: 0x4d0b88 <main_arena+1024> 0x4d0b98 <main_arena+1040>
0x4d0bb0 <main_arena+1064>: 0x4d0b98 <main_arena+1040> 0x4d0ba8 <main_arena+1056>
0x4d0bc0 <main_arena+1080>: 0x4d0ba8 <main_arena+1056> 0x4d0bb8 <main_arena+1072>
0x4d0bd0 <main_arena+1096>: 0x4d0bb8 <main_arena+1072> 0x4d0bc8 <main_arena+1088>
0x4d0be0 <main_arena+1112>: 0x4d0bc8 <main_arena+1088> 0x4d0bd8 <main_arena+1104>
0x4d0bf0 <main_arena+1128>: 0x4d0bd8 <main_arena+1104> 0x4d0be8 <main_arena+1120>
0x4d0c00 <main_arena+1144>: 0x4d0be8 <main_arena+1120> 0x4d0bf8 <main_arena+1136>
0x4d0c10 <main_arena+1160>: 0x4d0bf8 <main_arena+1136> 0x4d0c08 <main_arena+1152>
0x4d0c20 <main_arena+1176>: 0x4d0c08 <main_arena+1152> 0x4d0c18 <main_arena+1168>
0x4d0c30 <main_arena+1192>: 0x4d0c18 <main_arena+1168> 0x4d0c28 <main_arena+1184>
0x4d0c40 <main_arena+1208>: 0x4d0c28 <main_arena+1184> 0x4d0c38 <main_arena+1200>
0x4d0c50 <main_arena+1224>: 0x4d0c38 <main_arena+1200> 0x4d0c48 <main_arena+1216>
0x4d0c60 <main_arena+1240>: 0x4d0c48 <main_arena+1216> 0x4d0c58 <main_arena+1232>
0x4d0c70 <main_arena+1256>: 0x4d0c58 <main_arena+1232> 0x4d0c68 <main_arena+1248>
0x4d0c80 <main_arena+1272>: 0x4d0c68 <main_arena+1248> 0x4d0c78 <main_arena+1264>
0x4d0c90 <main_arena+1288>: 0x4d0c78 <main_arena+1264> 0x4d0c88 <main_arena+1280>

```

```

0x4d0ca0 <main_arena+1304>: 0x4d0c88 <main_arena+1280> 0x4d0c98 <main_arena+1296>
--Type <RET> for more, q to quit, c to continue without paging--
0x4d0cb0 <main_arena+1320>: 0x4d0c98 <main_arena+1296> 0x4d0ca8 <main_arena+1312>
0x4d0cc0 <main_arena+1336>: 0x4d0ca8 <main_arena+1312> 0x4d0cb8 <main_arena+1328>
0x4d0cd0 <main_arena+1352>: 0x4d0cb8 <main_arena+1328> 0x4d0cc8 <main_arena+1344>
0x4d0ce0 <main_arena+1368>: 0x4d0cc8 <main_arena+1344> 0x4d0cd8 <main_arena+1360>
0x4d0cf0 <main_arena+1384>: 0x4d0cd8 <main_arena+1360> 0x4d0ce8 <main_arena+1376>
0x4d0d00 <main_arena+1400>: 0x4d0ce8 <main_arena+1376> 0x4d0cf8 <main_arena+1392>
0x4d0d10 <main_arena+1416>: 0x4d0cf8 <main_arena+1392> 0x4d0d08 <main_arena+1408>
0x4d0d20 <main_arena+1432>: 0x4d0d08 <main_arena+1408> 0x4d0d18 <main_arena+1424>
0x4d0d30 <main_arena+1448>: 0x4d0d18 <main_arena+1424> 0x4d0d28 <main_arena+1440>
0x4d0d40 <main_arena+1464>: 0x4d0d28 <main_arena+1440> 0x4d0d38 <main_arena+1456>
0x4d0d50 <main_arena+1480>: 0x4d0d38 <main_arena+1456> 0x4d0d48 <main_arena+1472>
0x4d0d60 <main_arena+1496>: 0x4d0d48 <main_arena+1472> 0x4d0d58 <main_arena+1488>
0x4d0d70 <main_arena+1512>: 0x4d0d58 <main_arena+1488> 0x4d0d68 <main_arena+1504>
0x4d0d80 <main_arena+1528>: 0x4d0d68 <main_arena+1504> 0x4d0d78 <main_arena+1520>
0x4d0d90 <main_arena+1544>: 0x4d0d78 <main_arena+1520> 0x4d0d88 <main_arena+1536>
0x4d0da0 <main_arena+1560>: 0x4d0d88 <main_arena+1536> 0x4d0d98 <main_arena+1552>
0x4d0db0 <main_arena+1576>: 0x4d0d98 <main_arena+1552> 0x4d0da8 <main_arena+1568>
0x4d0dc0 <main_arena+1592>: 0x4d0da8 <main_arena+1568> 0x4d0db8 <main_arena+1584>
0x4d0dd0 <main_arena+1608>: 0x4d0db8 <main_arena+1584> 0x4d0dc8 <main_arena+1600>
0x4d0de0 <main_arena+1624>: 0x4d0dc8 <main_arena+1600> 0x4d0dd8 <main_arena+1616>
0x4d0df0 <main_arena+1640>: 0x4d0dd8 <main_arena+1616> 0x4d0de8 <main_arena+1632>
0x4d0e00 <main_arena+1656>: 0x4d0de8 <main_arena+1632> 0x4d0df8 <main_arena+1648>
0x4d0e10 <main_arena+1672>: 0x4d0df8 <main_arena+1648> 0x4d0e08 <main_arena+1664>
0x4d0e20 <main_arena+1688>: 0x4d0e08 <main_arena+1664> 0x4d0e18 <main_arena+1680>
0x4d0e30 <main_arena+1704>: 0x4d0e18 <main_arena+1680> 0x4d0e28 <main_arena+1696>
0x4d0e40 <main_arena+1720>: 0x4d0e28 <main_arena+1696> 0x4d0e38 <main_arena+1712>
0x4d0e50 <main_arena+1736>: 0x4d0e38 <main_arena+1712> 0x4d0e48 <main_arena+1728>
0x4d0e60 <main_arena+1752>: 0x4d0e48 <main_arena+1728> 0x4d0e58 <main_arena+1744>
0x4d0e70 <main_arena+1768>: 0x4d0e58 <main_arena+1744> 0x4d0e68 <main_arena+1760>
0x4d0e80 <main_arena+1784>: 0x4d0e68 <main_arena+1760> 0x4d0e78 <main_arena+1776>
0x4d0e90 <main_arena+1800>: 0x4d0e78 <main_arena+1776> 0x4d0e88 <main_arena+1792>
0x4d0ea0 <main_arena+1816>: 0x4d0e88 <main_arena+1792> 0x4d0ea8 <main_arena+1824>
0x4d0eb0 <main_arena+1832>: 0x4d0e98 <main_arena+1808> 0x4d0eb8 <main_arena+1840>
0x4d0ec0 <main_arena+1848>: 0x4d0ea8 <main_arena+1824> 0x4d0ec8 <main_arena+1856>
0x4d0ed0 <main_arena+1864>: 0x4d0eb8 <main_arena+1840> 0x4d0ed8 <main_arena+1872>
0x4d0ee0 <main_arena+1880>: 0x4d0ec8 <main_arena+1856> 0x4d0ee8 <main_arena+1888>
0x4d0ef0 <main_arena+1896>: 0x4d0ed8 <main_arena+1872> 0x4d0ef8 <main_arena+1904>
0x4d0f00 <main_arena+1912>: 0x4d0ee8 <main_arena+1888> 0x4d0f08 <main_arena+1920>
0x4d0f10 <main_arena+1928>: 0x4d0ef8 <main_arena+1904> 0x4d0f18 <main_arena+1936>
0x4d0f20 <main_arena+1944>: 0x4d0f08 <main_arena+1920> 0x4d0f28 <main_arena+1952>
0x4d0f30 <main_arena+1960>: 0x4d0f18 <main_arena+1936> 0x4d0f38 <main_arena+1968>
0x4d0f40 <main_arena+1976>: 0x4d0f28 <main_arena+1952> 0x4d0f38 <main_arena+1968>
0x4d0f50 <main_arena+1992>: 0x4d0f38 <main_arena+1968> 0x4d0f48 <main_arena+1984>
0x4d0f60 <main_arena+2008>: 0x4d0f48 <main_arena+1984> 0x4d0f58 <main_arena+2000>
0x4d0f70 <main_arena+2024>: 0x4d0f58 <main_arena+2000> 0x4d0f68 <main_arena+2016>
0x4d0f80 <main_arena+2040>: 0x4d0f68 <main_arena+2016> 0x4d0f78 <main_arena+2032>
0x4d0f90 <main_arena+2056>: 0x4d0f78 <main_arena+2032> 0x4d0f88 <main_arena+2048>
0x4d0fa0 <main_arena+2072>: 0x4d0f88 <main_arena+2048> 0x4d0f98 <main_arena+2064>
0x4d0fb0 <main_arena+2088>: 0x4d0f98 <main_arena+2064> 0x4d0fa8 <main_arena+2080>
0x4d0fc0 <main_arena+2104>: 0x4d0fa8 <main_arena+2080> 0x4d0fb8 <main_arena+2096>
--Type <RET> for more, q to quit, c to continue without paging--
0x4d0fd0 <main_arena+2120>: 0x4d0fb8 <main_arena+2096> 0x4d0fc8 <main_arena+2112>
0x4d0fe0 <main_arena+2136>: 0x4d0fc8 <main_arena+2112> 0x0
0x4dff0 <main_arena+2152>: 0x0 0x4d0788 <main_arena>
0x4d1000 <main_arena+2168>: 0x0 0x1
0x4d1010 <main_arena+2184>: 0x3f078 0x3f078
0x4d1020 <__morecore>: 0x421c08 <__default_morecore> 0x1
0x4d1030 <__libc_malloc_initialized>: 0xffffffffffff00000001
0x41cc00 <memalign_hook_ini>

```

```

0x4d1040 <__realloc_hook>:    0x41d688 <realloc_hook_ini>      0x0
0x4d1050 <LogFacility>: 0xfffffffff00000008      0xff00000002
0x4d1060 <cached_result.10628>: 0xffffffff      0xfffffd30bf6dd
0x4d1070 <program_invocation_name>: 0xfffffd30bf6db  0x10000
0x4d1080 <_dl_stack_flags>:   0x6      0x0
0x4d1090 <_dl_load_write_lock+8>: 0x0      0x1
0x4d10a0 <_dl_load_write_lock+24>: 0x0      0x0
0x4d10b0 <_dl_load_write_lock+40>: 0x0      0x0
0x4d10c0 <_dl_load_lock+8>:   0x0      0x1
0x4d10d0 <_dl_load_lock+24>: 0x0      0x0
0x4d10e0 <_dl_load_lock+40>:   0x0      0x42c6a0 <_dl_make_stack_executable>
0x4d10f0 <_dl_correct_cache_id>: 0x200000a03     0x4045a8 <__pthread_init_static_tls>
0x4d1100 <_dl_starting_up>:   0x1      0xfffffffffffffff
0x4d1110 <_dl_argv>:        0x4d1068 <program_invocation_short_name>      0x0
0x4d1120 <builtin_modules>: 0x48ad20      0x48ac30
0x4d1130 <builtin_modules+16>: 0x7fffffff00000001      0x48ac40
0x4d1140 <builtin_modules+32>: 0x0      0x0
0x4d1150 <builtin_modules+48>: 0x0      0x48ac30
0x4d1160 <builtin_modules+64>: 0x48ad20      0x7fffffff00000001
0x4d1170 <builtin_modules+80>: 0x48ac50      0x0
0x4d1180 <builtin_modules+96>: 0x0      0x0
0x4d1190 <builtin_modules+112>: 0x48ad20      0x48ac60
0x4d11a0 <builtin_modules+128>: 0x7fffffff00000001      0x48ac70
0x4d11b0 <builtin_modules+144>: 0x0      0x0
0x4d11c0 <builtin_modules+160>: 0x0      0x48ac60
0x4d11d0 <builtin_modules+176>: 0x48ad20      0x7fffffff00000001
0x4d11e0 <builtin_modules+192>: 0x48ac88      0x0
0x4d11f0 <builtin_modules+208>: 0x0      0x0
0x4d1200 <builtin_modules+224>: 0x48ad20      0x48aca0
0x4d1210 <builtin_modules+240>: 0x7fffffff00000001      0x48acb0
0x4d1220 <builtin_modules+256>: 0x0      0x0
0x4d1230 <builtin_modules+272>: 0x0      0x48aca0
0x4d1240 <builtin_modules+288>: 0x48ad20      0x7fffffff00000001
0x4d1250 <builtin_modules+304>: 0x48acc0      0x0
0x4d1260 <builtin_modules+320>: 0x0      0x0
0x4d1270 <builtin_modules+336>: 0x48acd0      0x48ad20
0x4d1280 <builtin_modules+352>: 0x7fffffff00000001      0x48ace0
0x4d1290 <builtin_modules+368>: 0x0      0x0
0x4d12a0 <builtin_modules+384>: 0x0      0x48ad20
0x4d12b0 <builtin_modules+400>: 0x48acd0      0x7fffffff00000001
0x4d12c0 <builtin_modules+416>: 0x48acf0      0x0
0x4d12d0 <builtin_modules+432>: 0x0      0x0
0x4d12e0 <builtin_modules+448>: 0x48ad00      0x48ad20

```

The output is in the following format:

```
address:    value1    value2
```

Because the size of each value is 8 bytes, the next address is +16 bytes or +10_{hex}. The addresses can have associated symbolic names:

```
address <name>:  value1  value2
```

Each value may also have an associated symbolic value:

```
address <name>:  value1 <name1>    value2
```

For example, from the output above:

```
0x4d1110 <_dl_argv>: 0x4d1068 <program_invocation_short_name> 0x0
```

11. Explore the contents of memory pointed to by `__nptl_nthreads`, `program_invocation_short_name`, and `_realloc_hook` addresses (`/x` is for hex, `/d` is for decimals, `/u` is for unsigned decimals, `/g` is for 64-bit values, `/w` is for 32-bit values, `/h` is for 16-bit values, `/b` is for byte values, `/a` is for addresses, `/c` and `/s` are for chars and strings):

```
(gdb) x/d &__nptl_nthreads  
0x4d0048 <__nptl_nthreads>: 6
```

```
(gdb) x/u 0x4d0048  
0x4d0048 <__nptl_nthreads>: 6
```

```
(gdb) x/wx 0x4d0048  
0x4d0048 <__nptl_nthreads>: 0x00000006
```

```
(gdb) x/gx 0x4d0048  
0x4d0048 <__nptl_nthreads>: 0x0000000000000006
```

```
(gdb) x/hx 0x4d0048  
0x4d0048 <__nptl_nthreads>: 0x0006
```

```
(gdb) x/bx 0x4d0048  
0x4d0048 <__nptl_nthreads>: 0x06
```

```
(gdb) x/a 0x4d1068  
0x4d1068 <program_invocation_short_name>: 0xfffffd30bf6dd
```

```
(gdb) x/a 0xfffffd30bf6dd  
0xfffffd30bf6dd: 0x4744580031707041
```

```
(gdb) x/s 0xfffffd30bf6dd  
0xfffffd30bf6dd: "App1"
```

```
(gdb) x/8c 0xfffffd30bf6dd  
0xfffffd30bf6dd: 65 'A' 112 'p' 112 'p' 49 '1' 0 '\000' 88 'X' 68 'D' 71 'G'
```

```
(gdb) x/10s 0xfffffd30bf6dd  
0xfffffd30bf6dd: "App1"  
0xfffffd30bf6e2: "XDG_SESSION_ID=6850"  
0xfffffd30bf6f6: "HOSTNAME=instance-20211109-2004"  
0xfffffd30bf716: "SELINUX_ROLE_REQUESTED="  
0xfffffd30bf72e: "TERM=xterm-256color"  
0xfffffd30bf742: "SHELL=/bin/bash"  
0xfffffd30bf752: "HISTSIZE=1000"  
0xfffffd30bf760: "SSH_CLIENT=37.228.238.120 61099 22"  
0xfffffd30bf783: "SELINUX_USE_CURRENT_RANGE="  
0xfffffd30bf79e: "SSH_TTY=/dev/pts/1"
```

```
(gdb) x/a &_realloc_hook  
0x4d1040 <_realloc_hook>: 0x41d688 <realloc_hook_ini>
```

```
(gdb) x/10i 0x41d688  
0x41d688 <realloc_hook_ini>: stp x29, x30, [sp, #-112]!  
0x41d68c <realloc_hook_ini+4>: mov x29, sp  
0x41d690 <realloc_hook_ini+8>: stp x25, x26, [sp, #64]  
0x41d694 <realloc_hook_ini+12>: adrp x25, 0x4d0000  
0x41d698 <realloc_hook_ini+16>: add x2, x25, #0x718
```

```

0x41d69c <realloc_hook_ini+20>:    stp    x21, x22, [sp, #32]
0x41d6a0 <realloc_hook_ini+24>:    ldr    w3, [x2, #2328]
0x41d6a4 <realloc_hook_ini+28>:    ldr    x21, 0x41da48
0x41d6a8 <realloc_hook_ini+32>:    ldr    x2, 0x41da40
0x41d6ac <realloc_hook_ini+36>:    stp    x19, x20, [sp, #16]

```

Note: We see that a hook function is installed for *realloc*. Please find the following documentation for hook functions here:

https://www.gnu.org/software/libc/manual/html_node/Hooks-for-Malloc.html

12. Explore the contents of memory pointed to by *environ* variable address:

```

(gdb) x/a &environ
0x4d64c8 <environ>: 0xfffffd30b8888

(gdb) x/10a 0xfffffd30b8888
0xfffffd30b8888: 0xfffffd30bf6e2 0xfffffd30bf6f6
0xfffffd30b8898: 0xfffffd30bf716 0xfffffd30bf72e
0xfffffd30b88a8: 0xfffffd30bf742 0xfffffd30bf752
0xfffffd30b88b8: 0xfffffd30bf760 0xfffffd30bf783
0xfffffd30b88c8: 0xfffffd30bf79e 0xfffffd30bf7b1

(gdb) x/10s 0xfffffd30bf6e2
0xfffffd30bf6e2: "XDG_SESSION_ID=6850"
0xfffffd30bf6f6: "HOSTNAME=instance-20211109-2004"
0xfffffd30bf716: "SELINUX_ROLE_REQUESTED="
0xfffffd30bf72e: "TERM=xterm-256color"
0xfffffd30bf742: "SHELL=/bin/bash"
0xfffffd30bf752: "HISTSIZE=1000"
0xfffffd30bf760: "SSH_CLIENT=37.228.238.120 61099 22"
0xfffffd30bf783: "SELINUX_USE_CURRENT_RANGE="
0xfffffd30bf79e: "SSH_TTY=/dev/pts/1"
0xfffffd30bf7b1: "USER=opc"

```

13. Now we look at how to perform a memory search. It is not possible to search in the entire virtual memory, only in the valid regions.

```

(gdb) find /g 0x004d0030, 0x005d0030, 6
0x4d0048 <__nptl_nthreads>
0x4d1080 <_dl_stack_flags>
0x4d7e00 <_dl_phnum>
warning: Unable to access 16000 bytes of target memory at 0x4dfb08, halting search.
3 patterns found.

```

```

(gdb) x/gd 0x4d0048
0x4d0048 <__nptl_nthreads>: 6

(gdb) find 0xfffffd30bf6e2, +1000, "bash"
0xfffffd30bf74d
1 pattern found.

```

```

(gdb) x/s 0xfffffd30bf74d-11
0xfffffd30bf742: "SHELL=/bin/bash"

```

Note: "bash" is considered a null-terminated array of characters for the search. To search for a string sequence without a null terminator, use a sequence of characters:

```
(gdb) find 0xfffffd30bf6e2, +1000, "bin"
Pattern not found.

(gdb) find 0xfffffd30bf6e2, +1000, 'b', 'i', 'n'
0xfffffd30bf749
1 pattern found.
```

14. Get the list of loaded modules:

```
(gdb) info sharedlibrary
No shared libraries loaded at this time.
```

Note: We don't see any shared libraries because they were statically linked. We also created the version of a dynamically linked *App1.shared* executable. If we load its core dump *App1.shared.core.184724* from the App1S directory, we see the list of shared libraries:

```
~/ALCDA2/A64/App1S$ gdb -c App1.shared.core.184724 -se App1.shared
GNU gdb (Ubuntu 12.1-0ubuntu1~22.04) 12.1
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "aarch64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
  <http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from App1.shared...
(No debugging symbols found in App1.shared)
[New LWP 184724]
[New LWP 184725]
[New LWP 184726]
[New LWP 184727]
[New LWP 184728]
[New LWP 184729]
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/aarch64-linux-gnu/libthread_db.so.1".
Core was generated by `./App1.shared'.
#0 0x0000ffff81451924 in __GI_clock_nanosleep (clock_id=<optimized out>, clock_id@entry=0,
    flags=flags@entry=0, req=req@entry=0xfffffc23e78a8, rem=rem@entry=0xfffffc23e78a8)
    at ../sysdeps/unix/sysv/linux/clock_nanosleep.c:78
78     ../sysdeps/unix/sysv/linux/clock_nanosleep.c: No such file or directory.
[Current thread is 1 (Thread 0xfffff81585e80 (LWP 184724))]
```

```
(gdb) set style enabled off
```

```
(gdb) info sharedlibrary
From          To            Syms Read  Shared Object Library
0x0000ffff813c7040 0x0000ffff814d3f20 Yes      /lib/aarch64-linux-gnu/libc.so.6
0x0000ffff81551c40 0x0000ffff81570064 Yes      /lib/ld-linux-aarch64.so.1
```

15. Disassemble the *bar_one* function and follow the indirect *sleep* function call:

```
(gdb) disassemble bar_one
Dump of assembler code for function bar_one:
0x0000aaaad0be0894 <+0>:    stp      x29, x30, [sp, #-16]!
0x0000aaaad0be0898 <+4>:    mov      x29, sp
0x0000aaaad0be089c <+8>:    mov      w0, #0xffffffff          // #-1
0x0000aaaad0be08a0 <+12>:   bl      0xaaaad0be0710 <sleep@plt>
0x0000aaaad0be08a4 <+16>:   ldp      x29, x30, [sp], #16
0x0000aaaad0be08a8 <+20>:   ret
End of assembler dump.
```

```
(gdb) disassemble 0xaaaad0be0710
Dump of assembler code for function sleep@plt:
0x0000aaaad0be0710 <+0>:    adrp     x16, 0xaaaad0bf1000
0x0000aaaad0be0714 <+4>:    ldr      x17, [x16, #4000]
0x0000aaaad0be0718 <+8>:    add      x16, x16, #0xfa0
0x0000aaaad0be071c <+12>:   br      x17
End of assembler dump.
```

```
(gdb) x/a 0xaaaad0bf1000+4000
0xaaaad0bf1fa0 <sleep@got.plt>: 0xfffff81456970 <__sleep>
```

Note: Since GDB gets shared library images from your analysis system which do not correspond to shared libraries from the crash system, most likely you get some random symbolic information (and, also, an invalid backtrace from the **bt** command). This is an example using *App1.shared.core.22442* from the *App1* directory:

```
(gdb) bt
#0 0x0000ffff0496dd64 in ?? ()
Backtrace stopped: previous frame identical to this frame (corrupt stack?)
```

```
(gdb) info sharedlibrary
From           To             Syms Read  Shared Object Library
               No            /lib64/libpthread.so.0
               No            /lib64/libc.so.6
0x0000ffff04ab5bf8 0x0000ffff04ad401c Yes       /lib/ld-linux-aarch64.so.1
```

```
(gdb) disassemble bar_one
Dump of assembler code for function bar_one:
0x0000000000400728 <+0>:    stp      x29, x30, [sp, #-16]!
0x000000000040072c <+4>:    mov      x29, sp
0x0000000000400730 <+8>:    mov      w0, #0xffffffff          // #-1
0x0000000000400734 <+12>:   bl      0x400580 <sleep@plt>
0x0000000000400738 <+16>:   ldp      x29, x30, [sp], #16
0x000000000040073c <+20>:   ret
End of assembler dump.
```

```
(gdb) disassemble 0x400580
Dump of assembler code for function sleep@plt:
0x0000000000400580 <+0>:    adrp     x16, 0x420000 <_libc_start_main@got.plt>
0x0000000000400584 <+4>:    ldr      x17, [x16, #8]
0x0000000000400588 <+8>:    add      x16, x16, #0x8
0x000000000040058c <+12>:   br      x17
End of assembler dump.
```

```
(gdb) x/a 0x420000+8
0x420008 <sleep@got.plt>: 0xfffff0496d904
```

Note: You need the original shared library images and debug symbol files from the problem system. To get the right results for this exercise, you can recreate the *App1.shared* core dump (see *main.c* for build instructions if necessary).

16. *App1.shared.pmap.184724* also shows library memory regions:

```
(gdb) q
```

```
~/ALCDA2/A64/App1$ cat App1.shared.pmap.184724
184724: ./App1.shared
0000aaaad0be0000      4K r-x--  App1.shared
0000aaaad0bf1000      4K r----  App1.shared
0000aaaad0bf2000      4K rw---  App1.shared
0000aaaaafe503000    132K rw---  [ anon ]
0000fffff7eb50000     64K -----  [ anon ]
0000fffff7eb60000   8192K rw---  [ anon ]
0000fffff7f360000     64K -----  [ anon ]
0000fffff7f370000   8192K rw---  [ anon ]
0000fffff7fb70000     64K -----  [ anon ]
0000fffff7fb80000   8192K rw---  [ anon ]
0000fffff80380000     64K -----  [ anon ]
0000fffff80390000   8192K rw---  [ anon ]
0000fffff80b90000     64K -----  [ anon ]
0000fffff80ba0000   8192K rw---  [ anon ]
0000fffff813a0000  1572K r-x--  libc.so.6
0000fffff81529000     60K -----  libc.so.6
0000fffff81538000     16K r----  libc.so.6
0000fffff8153c000      8K rw---  libc.so.6
0000fffff8153e000     48K rw---  [ anon ]
0000fffff81550000   172K r-x--  ld-linux-aarch64.so.1
0000fffff81585000      8K rw---  [ anon ]
0000fffff81587000      8K r----  [ anon ]
0000fffff81589000      4K r-x--  [ anon ]
0000fffff8158a000      8K r----  ld-linux-aarch64.so.1
0000fffff8158c000      8K rw---  ld-linux-aarch64.so.1
0000fffffc23c8000    132K rw---  [ stack ]
total                  43468K
```

Exercise A1 (A64, WinDbg Preview)

Goal: Learn how to list stack traces, disassemble functions, check their correctness, dump data, get environment.

Patterns: Manual Dump; Stack Trace; Stack Trace Collection; Annotated Disassembly; Paratext; Not My Version; Environment Hint.

1. Launch WinDbg Preview.
2. Load a core dump *App1.core.21174* from the A64\App1 folder:

```
Microsoft (R) Windows Debugger Version 10.0.25111.1000 AMD64
Copyright (c) Microsoft Corporation. All rights reserved.
```

```
Loading Dump File [C:\ALCDA2\A64\App1\App1.core.21174]
64-bit machine not using 64-bit API

***** Path validation summary *****
Response           Time (ms)    Location
Deferred          srv*

Symbol search path is: srv*
Executable search path is:
Generic Unix Version 0 UP Free ARM 64-bit (AArch64)
Machine Name:
System Uptime: not available
Process Uptime: not available
..
*** WARNING: Unable to verify timestamp for App1
App1+0xc9b4:
00000000`0040c9b4 d4000001 svc      #0
```

3. Set logging to a file in case of lengthy output from some commands:

```
0:000> .logopen C:\ALCDA2\A64\App1\App1.log
Opened log file 'C:\ALCDA2\A64\App1\App1.log'
```

4. Specify the dump folder as the symbol path and reload symbols:

```
0:000> .sympath+ C:\ALCDA2\A64\App1\
Symbol search path is: srv*;C:\ALCDA2\A64\App1\
Expanded Symbol search path is:
cache*;SRV*https://msdl.microsoft.com/download/symbols;c:\alcda2\app1\

***** Path validation summary *****
Response           Time (ms)    Location
Deferred          srv*
OK                C:\ALCDA2\A64\App1\
*** WARNING: Unable to verify timestamp for App1
```

```

0:000> .reload
..
*** WARNING: Unable to verify timestamp for App1

***** Symbol Loading Error Summary *****
Module name      Error
App1            The system cannot find the file specified

You can troubleshoot most symbol related issues by turning on symbol loading diagnostics (!sym noisy) and repeating the command that caused symbols to be loaded.
You should also verify that your symbol search path (.sympath) is correct.

```

Note: We ignore warnings and errors as they are not relevant for now.

5. List all threads:

```

0:000> ~
Unable to get thread data for thread 0
. 0 Id: 52b6.52b7 Suspend: 0 Teb: 00000000`00000000 Unfrozen
Unable to get thread data for thread 1
  1 Id: 52b6.52b8 Suspend: 0 Teb: 00000000`00000000 Unfrozen
Unable to get thread data for thread 2
  2 Id: 52b6.52b9 Suspend: 0 Teb: 00000000`00000000 Unfrozen
Unable to get thread data for thread 3
  3 Id: 52b6.52ba Suspend: 0 Teb: 00000000`00000000 Unfrozen
Unable to get thread data for thread 4
  4 Id: 52b6.52bb Suspend: 0 Teb: 00000000`00000000 Unfrozen
Unable to get thread data for thread 5
  5 Id: 52b6.52b6 Suspend: 0 Teb: 00000000`00000000 Unfrozen

```

Note: WinDbg uses the same output format as for Windows memory dumps. Therefore, some data is either reported as errors or shows 0 or NULL pointer values. However, we see process and threads IDs in the format PID.TID:

```

0:000> .formats 52b6
Evaluate expression:
  Hex: 00000000`000052b6
  Decimal: 21174
  Octal: 000000000000000051266
  Binary: 00000000 00000000 00000000 00000000 00000000 01010010 10110110
  Chars: .....R.
  Time: Thu Jan 1 05:52:54 1970
  Float: low 2.96711e-041 high 0
  Double: 1.04613e-319

```

```

0:000> ? 52b6
Evaluate expression: 21174 = 00000000`000052b6

```

6. Get the current thread stack trace:

```

0:000> k
# Child-SP      RetAddr          Call Site
00 0000ffff`cd38e5f0 00000000`00424cb4  App1!_libc_nanosleep+0x24
01 0000ffff`cd38e630 00000000`004031f8  App1!sleep+0x110
02 0000ffff`cd38e820 00000000`0040320c  App1!bar_one+0x10
03 0000ffff`cd38e830 00000000`00403224  App1!foo_one+0xc
04 0000ffff`cd38e840 00000000`00404c34  App1!thread_one+0x10
05 0000ffff`cd38e860 00000000`00429b60  App1!start_thread+0xb4

```

```
06 0000ffff`cd38e990 ffffffff`fffffff App1!thread_start+0x30
07 0000ffff`cd38e990 00000000`00000000 0xffffffff`fffffff
```

7. Get all thread stack traces:

```
0:000> ~*k
```

```
Unable to get thread data for thread 0
. 0 Id: 52b6.52b7 Suspend: 0 Teb: 00000000`00000000 Unfrozen
# Child-SP RetAddr Call Site
00 0000ffff`cd38e5f0 00000000`00424cb4 App1!_libc_nanosleep+0x24
01 0000ffff`cd38e630 00000000`004031f8 App1!sleep+0x110
02 0000ffff`cd38e820 00000000`0040320c App1!bar_one+0x10
03 0000ffff`cd38e830 00000000`00403224 App1!foo_one+0xc
04 0000ffff`cd38e840 00000000`00404c34 App1!thread_one+0x10
05 0000ffff`cd38e860 00000000`00429b60 App1!start_thread+0xb4
06 0000ffff`cd38e990 ffffffff`fffffff App1!thread_start+0x30
07 0000ffff`cd38e990 00000000`00000000 0xffffffff`fffffff

Unable to get thread data for thread 1
1 Id: 52b6.52b8 Suspend: 0 Teb: 00000000`00000000 Unfrozen
# Child-SP RetAddr Call Site
00 0000ffff`ccb7e5f0 00000000`00424cb4 App1!_libc_nanosleep+0x24
01 0000ffff`ccb7e630 00000000`00403240 App1!sleep+0x110
02 0000ffff`ccb7e820 00000000`00403254 App1!bar_two+0x10
03 0000ffff`ccb7e830 00000000`0040326c App1!foo_two+0xc
04 0000ffff`ccb7e840 00000000`00404c34 App1!thread_two+0x10
05 0000ffff`ccb7e860 00000000`00429b60 App1!start_thread+0xb4
06 0000ffff`ccb7e990 ffffffff`fffffff App1!thread_start+0x30
07 0000ffff`ccb7e990 00000000`00000000 0xffffffff`fffffff

Unable to get thread data for thread 2
2 Id: 52b6.52b9 Suspend: 0 Teb: 00000000`00000000 Unfrozen
# Child-SP RetAddr Call Site
00 0000ffff`cc36e5f0 00000000`00424cb4 App1!_libc_nanosleep+0x24
01 0000ffff`cc36e630 00000000`00403288 App1!sleep+0x110
02 0000ffff`cc36e820 00000000`0040329c App1!bar_three+0x10
03 0000ffff`cc36e830 00000000`004032b4 App1!foo_three+0xc
04 0000ffff`cc36e840 00000000`00404c34 App1!thread_three+0x10
05 0000ffff`cc36e860 00000000`00429b60 App1!start_thread+0xb4
06 0000ffff`cc36e990 ffffffff`fffffff App1!thread_start+0x30
07 0000ffff`cc36e990 00000000`00000000 0xffffffff`fffffff

Unable to get thread data for thread 3
3 Id: 52b6.52ba Suspend: 0 Teb: 00000000`00000000 Unfrozen
# Child-SP RetAddr Call Site
00 0000ffff`ccb5e5f0 00000000`00424cb4 App1!_libc_nanosleep+0x24
01 0000ffff`ccb5e630 00000000`004032d0 App1!sleep+0x110
02 0000ffff`ccb5e820 00000000`004032e4 App1!bar_four+0x10
03 0000ffff`ccb5e830 00000000`004032fc App1!foo_four+0xc
04 0000ffff`ccb5e840 00000000`00404c34 App1!thread_four+0x10
05 0000ffff`ccb5e860 00000000`00429b60 App1!start_thread+0xb4
06 0000ffff`ccb5e990 ffffffff`fffffff App1!thread_start+0x30
07 0000ffff`ccb5e990 00000000`00000000 0xffffffff`fffffff

Unable to get thread data for thread 4
4 Id: 52b6.52bb Suspend: 0 Teb: 00000000`00000000 Unfrozen
# Child-SP RetAddr Call Site
00 0000ffff`cb34e5f0 00000000`00424cb4 App1!_libc_nanosleep+0x24
01 0000ffff`cb34e630 00000000`00403318 App1!sleep+0x110
```

```

02 0000ffff`cb34e820 00000000`0040332c      App1!bar_five+0x10
03 0000ffff`cb34e830 00000000`00403344      App1!foo_five+0xc
04 0000ffff`cb34e840 00000000`00404c34      App1!thread_five+0x10
05 0000ffff`cb34e860 00000000`00429b60      App1!start_thread+0xb4
06 0000ffff`cb34e990 ffffffff`fffffff        App1!thread_start+0x30
07 0000ffff`cb34e990 00000000`00000000      0xffffffff`fffffff

Unable to get thread data for thread 5
 5 Id: 52b6.52b6 Suspend: 0 Teb: 00000000`00000000 Unfrozen
 # Child-SP          RetAddr           Call Site
00 0000ffff`d30b8490 00000000`00424cb4      App1!_libc_nanosleep+0x24
01 0000ffff`d30b84d0 00000000`004033e0      App1!sleep+0x110
02 0000ffff`d30b86c0 00000000`0040ec4c      App1!main+0x90
03 0000ffff`d30b8710 00000000`00403090      App1!_libc_start_main+0x304
04 0000ffff`d30b8870 00000000`00000000      App1!start+0x4c

```

8. Switch to thread #1 (threads are numbered from 0) and get its stack trace:

```

0:000> ~1s
App1!_libc_nanosleep+0x24:
00000000`0040c9b4 d4000001 svc          #0

0:001> k
# Child-SP          RetAddr           Call Site
00 0000ffff`ccb7e5f0 00000000`00424cb4      App1!_libc_nanosleep+0x24
01 0000ffff`ccb7e630 00000000`00403240      App1!sleep+0x110
02 0000ffff`ccb7e820 00000000`00403254      App1!bar_two+0x10
03 0000ffff`ccb7e830 00000000`0040326c      App1!foo_two+0xc
04 0000ffff`ccb7e840 00000000`00404c34      App1!thread_two+0x10
05 0000ffff`ccb7e860 00000000`00429b60      App1!start_thread+0xb4
06 0000ffff`ccb7e990 ffffffff`fffffff        App1!thread_start+0x30
07 0000ffff`ccb7e990 00000000`00000000      0xffffffff`fffffff

```

9. Check that *bar_two* called *sleep* function by comparing the return address on the call stack from the disassembly output:

```

0:001> uf bar_two
App1!bar_two:
00000000`00403230 a9bf7bfd stp          fp,lr,[sp,#-0x10]!
00000000`00403234 910003fd mov          fp,sp
00000000`00403238 12800000 mov         w0,#-1
00000000`0040323c 9400865a b1          App1!sleep (00000000`00424ba4)
00000000`00403240 a8c17bfd ldp          fp,lr,[sp],#0x10
00000000`00403244 d65f03c0 ret

```

Another way to do that is to disassemble backward the return address and check if the last instruction is BL:

```

0:001> ub 00000000`00403240
App1!thread_one+0xc:
00000000`00403220 97fffff8 b1          App1!foo_one (00000000`00403200)
00000000`00403224 d2800000 mov          x0,#0
00000000`00403228 a8c27bfd ldp          fp,lr,[sp],#0x20
00000000`0040322c d65f03c0 ret
App1!bar_two:
00000000`00403230 a9bf7bfd stp          fp,lr,[sp,#-0x10]!
00000000`00403234 910003fd mov          fp,sp
00000000`00403238 12800000 mov         w0,#-1
00000000`0040323c 9400865a b1          App1!sleep (00000000`00424ba4)

```

10. Get App1 data section from the contents of pmap (App1.pmap.21174):

```
21174: ./App1
000000000400000 768K r-x-- App1
0000000004c0000 128K rw--- App1
0000000001fa0000 256K rw--- [ anon ]
0000fffccab40000 64K ----- [ anon ]
0000fffccab50000 8192K rw--- [ anon ]
0000fffccb350000 64K ----- [ anon ]
0000fffccb360000 8192K rw--- [ anon ]
0000fffccb60000 64K ----- [ anon ]
0000fffccb70000 8192K rw--- [ anon ]
0000fffccc370000 64K ----- [ anon ]
0000fffccc380000 8192K rw--- [ anon ]
0000fffccb80000 64K ----- [ anon ]
0000fffccb90000 8192K rw--- [ anon ]
0000fffcd390000 64K r---- [ anon ]
0000fffcd3a0000 64K r-x-- [ anon ]
0000ffffd3090000 192K rw--- [ stack ]
total 42752K
```

11. Compare with the region information in the core dump:

```
0:001> !address

Mapping file section regions...
Mapping module regions...



| BaseAddress     | EndAddress+1   | RegionSize     | Type        | State          | Protect           | Usage                                      |
|-----------------|----------------|----------------|-------------|----------------|-------------------|--------------------------------------------|
| + 0`00000000    | 0`00400000     | 0`00400000     |             |                |                   | <unknown>                                  |
| + 0`00400000    | 0`004e0000     | 0`000c0000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_EXECUTE_READ | Image [App1; "/home/opc/ALCDA2/App1/App1"] |
| + 0`004c0000    | 0`004e0000     | 0`00020000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READWRITE    | Image [App1; "/home/opc/ALCDA2/App1/App1"] |
| + 0`004e0000    | 0`01fa0000     | 0`01ac0000     |             |                |                   | <unknown>                                  |
| + 0`01fa0000    | 0`01fe0000     | 0`00040000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READWRITE    | <unknown> [.....]                          |
| + 0`01fe0000    | ffffc`cab40000 | ffffc`cab60000 |             |                |                   | <unknown>                                  |
| + fffc`cab40000 | fffc`cab50000  | 0`00010000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READONLY     | <unknown> [.....]                          |
| + fffc`cab50000 | fffc`cb350000  | 0`00800000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READWRITE    | <unknown> [.....]                          |
| + fffc`cb350000 | fffc`cb360000  | 0`00010000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READONLY     | <unknown> [.....]                          |
| + fffc`cb360000 | fffc`ccb60000  | 0`00800000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READWRITE    | <unknown> [.....]                          |
| + fffc`ccb60000 | fffc`ccb70000  | 0`00010000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READONLY     | <unknown> [.....]                          |
| + fffc`ccb70000 | fffc`cc370000  | 0`00800000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READWRITE    | <unknown> [.....]                          |
| + ffc`cc370000  | fffc`cc380000  | 0`00010000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READONLY     | <unknown> [.....]                          |
| + ffc`cc380000  | fffc`ccb80000  | 0`00800000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READWRITE    | <unknown> [.....]                          |
| + ffc`ccb80000  | fffc`ccb90000  | 0`00010000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READONLY     | <unknown> [.....]                          |
| + ffc`ccb90000  | fffc`cd390000  | 0`00800000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_READWRITE    | <unknown> [.....]                          |
| + ffc`cd390000  | fffc`cd3a0000  | 0`00010000     |             |                |                   | <unknown>                                  |
| + ffc`cd3a0000  | fffc`d3090000  | 0`00010000     | MEM_PRIVATE | MEM_COMMIT     | PAGE_EXECUTE_READ | Image [linux_vdso_so; "linux-vdso.so.1"]   |
| + ffc`d3090000  | fffff`d30c0000 | 3`05ce0000     |             |                |                   | <unknown> [.....]                          |
| + ffff`d30c0000 | 0`00030000     | MEM_PRIVATE    | MEM_COMMIT  | PAGE_READWRITE |                   | <unknown> [.....]                          |


```

12. Dump the data region with possible symbolic information (we truncated the output):

```
0:001> dps 0`004c0000 0`004e0000
[...]
00000000`004d0fe8 00000000`00000000
00000000`004d0ff0 00000000`00000000
00000000`004d0ff8 00000000`004d0788 App1!main_arena
00000000`004d1000 00000000`00000000
00000000`004d1008 00000000`00000001
00000000`004d1010 00000000`0003f078
00000000`004d1018 00000000`0003f078
00000000`004d1020 00000000`00421c08 App1!_default_morecore
00000000`004d1028 00000000`00000001
00000000`004d1030 ffffffff`00000001
00000000`004d1038 00000000`0041cc00 App1!memalign_hook_ini
00000000`004d1040 00000000`0041d688 App1!realloc_hook_ini
00000000`004d1048 00000000`00000000
00000000`004d1050 ffffffff`00000008
00000000`004d1058 000000ff`00000002
00000000`004d1060 00000000`ffffffff
```

```

00000000`004d1068 0000ffff`d30bf6dd
00000000`004d1070 0000ffff`d30bf6db
00000000`004d1078 00000000`00010000
00000000`004d1080 00000000`00000006
00000000`004d1088 00000000`00000000
00000000`004d1090 00000000`00000000
00000000`004d1098 00000000`00000001
00000000`004d10a0 00000000`00000000
00000000`004d10a8 00000000`00000000
00000000`004d10b0 00000000`00000000
00000000`004d10b8 00000000`00000000
00000000`004d10c0 00000000`00000000
00000000`004d10c8 00000000`00000001
00000000`004d10d0 00000000`00000000
00000000`004d10d8 00000000`00000000
00000000`004d10e0 00000000`00000000
00000000`004d10e8 00000000`0042c6a0 App1!dl_make_stack_executable
00000000`004d10f0 00000002`00000a03
00000000`004d10f8 00000000`004045a8 App1!_pthread_init_static_tls
00000000`004d1100 00000000`00000001
00000000`004d1108 ffffffff`ffffffff
00000000`004d1110 00000000`004d1068 App1!_progname
00000000`004d1118 00000000`00000000
00000000`004d1120 00000000`0048ad20 App1!$d+0xe0
00000000`004d1128 00000000`0048ac30 App1!$d+0x38
00000000`004d1130 7fffffff`00000001
00000000`004d1138 00000000`0048ac40 App1!$d
00000000`004d1140 00000000`00000000
00000000`004d1148 00000000`00000000
00000000`004d1150 00000000`00000000
[...]

```

The output is in the following format:

```
address  value
```

Some values may have associated symbols in the format module!name+offset:

```
address  value  symbol
```

For example, from the output above:

```
00000000`004d1110 00000000`004d1068 App1!_progname
```

To list all values with symbols, we can use the **dps** command (it doesn't show the value addresses):

```
0:001> dps 0`004c0000 0`004e0000
00000000`004d6e70 App1!res
00000000`004d13c0 App1!nl_global_locale
00000000`004d13c0 App1!nl_global_locale
00000000`004d13e0 App1!nl_global_locale+0x20
00000000`004d13c8 App1!nl_global_locale+0x8
00000000`00403190 App1!frame_dummy
00000000`00403140 App1!_do_global_dtors_aux
00000000`00402ffc App1!fini
00000000`0048a2d0 App1!$d+0x20
00000000`0048a2f0 App1!$d+0x40
00000000`0048a308 App1!$d+0x58
00000000`0048a320 App1!$d+0x70
00000000`0048a330 App1!$d+0x80
```

```
00000000`0048a348 App1!$d+0x98
00000000`0048a358 App1!$d+0xa8
00000000`0048a368 App1!$d+0xb8
00000000`0048a380 App1!$d+0xd0
00000000`0048a398 App1!$d+0xe8
00000000`0048a3c0 App1!$d+0x110
00000000`0048a3d8 App1!$d+0x128
00000000`0048a3e8 App1!$d+0x138
00000000`0048a400 App1!$d+0x150
00000000`0048a418 App1!$d+0x168
00000000`0048a438 App1!$d+0x188
00000000`0048a450 App1!$d+0x1a0
00000000`0048a470 App1!$d+0x1c0
00000000`0048a488 App1!$d+0x1d8
00000000`0048a4a0 App1!$d+0x1f0
00000000`0048a4b8 App1!$d+0x208
00000000`0048a4d0 App1!$d+0x220
00000000`00409a50 App1!_pthread_key_create
00000000`004231c0 App1!_memmove_generic
00000000`004231d0 App1!_memcpy_generic
00000000`00423fc0 App1!_memset_generic
00000000`00424480 App1!_strlen_generic
00000000`00424480 App1!_strlen_generic
00000000`004d0038 App1!stack_cache
00000000`004d0038 App1!stack_cache
00000000`004d5eb0 App1!initial
00000000`00486b88 App1!_gcc_personality_v0
00000000`004d0088 App1!IO_2_1_stderr_
00000000`004d02b0 App1!IO_2_1_stdout_
00000000`004d6428 App1!IO_stdfile_2_lock
00000000`004d0168 App1!IO_wide_data_2
00000000`004a1950 App1!IO_file_jumps
00000000`004a1800 App1!IO_wfile_jumps
00000000`004d04d8 App1!IO_2_1_stdin_
00000000`004d6438 App1!IO_stdfile_1_lock
00000000`004d0390 App1!IO_wide_data_1
00000000`004a1950 App1!IO_file_jumps
00000000`004a1800 App1!IO_wfile_jumps
00000000`004d6448 App1!IO_stdfile_0_lock
00000000`004d05b8 App1!IO_wide_data_0
00000000`004a1950 App1!IO_file_jumps
00000000`004a1800 App1!IO_wfile_jumps
00000000`004d0088 App1!IO_2_1_stderr_
00000000`004d02b0 App1!IO_2_1_stdout_
00000000`004d04d8 App1!IO_2_1_stdin_
00000000`004d07e8 App1!main_arena+0x60
00000000`004d07e8 App1!main_arena+0x60
00000000`004d07f8 App1!main_arena+0x70
00000000`004d07f8 App1!main_arena+0x70
00000000`004d0808 App1!main_arena+0x80
00000000`004d0808 App1!main_arena+0x80
00000000`004d0818 App1!main_arena+0x90
00000000`004d0818 App1!main_arena+0x90
00000000`004d0828 App1!main_arena+0xa0
00000000`004d0828 App1!main_arena+0xa0
00000000`004d0838 App1!main_arena+0xb0
00000000`004d0838 App1!main_arena+0xb0
00000000`004d0848 App1!main_arena+0xc0
00000000`004d0848 App1!main_arena+0xc0
00000000`004d0858 App1!main_arena+0xd0
```

```
00000000`004d0858 App1!main_arena+0xd0
00000000`004d0868 App1!main_arena+0xe0
00000000`004d0868 App1!main_arena+0xe0
00000000`004d0878 App1!main_arena+0xf0
00000000`004d0878 App1!main_arena+0xf0
00000000`004d0888 App1!main_arena+0x100
00000000`004d0888 App1!main_arena+0x100
00000000`004d0898 App1!main_arena+0x110
[...]
00000000`004d0fc8 App1!main_arena+0x840
00000000`004d0788 App1!main_arena
00000000`00421c08 App1!_default_morecore
00000000`0041cc00 App1!memalign_hook_ini
00000000`0041d688 App1!realloc_hook_ini
00000000`0042c6a0 App1!dl_make_stack_executable
00000000`004045a8 App1!_pthread_init_static_tls
00000000`004d1068 App1!_progname
00000000`0048ad20 App1!$d+0xe0
00000000`0048ac30 App1!$d+0x38
00000000`0048ac40 App1!$d
00000000`0048ac30 App1!$d+0x38
00000000`0048ad20 App1!$d+0xe0
00000000`0048ac50 App1!$d+0x10
00000000`0048ad20 App1!$d+0xe0
00000000`0048ac60 App1!$d+0x20
00000000`0048ac70 App1!$d+0x30
00000000`0048ac60 App1!$d+0x20
00000000`0048ad20 App1!$d+0xe0
00000000`0048ac88 App1!$d+0x48
00000000`0048ad20 App1!$d+0xe0
00000000`0048aca0 App1!$d+0x60
00000000`0048acb0 App1!$d+0x70
00000000`0048aca0 App1!$d+0x60
00000000`0048ad20 App1!$d+0xe0
00000000`0048acc0 App1!$d+0x80
00000000`0048acd0 App1!$d+0x90
00000000`0048ad20 App1!$d+0xe0
00000000`0048ace0 App1!$d+0xa0
00000000`0048ad20 App1!$d+0xe0
00000000`0048acd0 App1!$d+0x90
00000000`0048acf0 App1!$d+0xb0
00000000`0048ad00 App1!$d+0xc0
00000000`0048ad20 App1!$d+0xe0
00000000`0048ad18 App1!$d+0xd8
00000000`0048ad20 App1!$d+0xe0
00000000`0048ad00 App1!$d+0xc0
00000000`0048ad30 App1!$d+0xf0
00000000`0048ad48 App1!$d+0x108
00000000`0048ad20 App1!$d+0xe0
00000000`0048ad58 App1!$d+0x118
00000000`0048ad20 App1!$d+0xe0
00000000`0048ad48 App1!$d+0x108
00000000`0048ad70 App1!$d+0x130
00000000`0048b888 App1!nl_C_LC_CTYPE
00000000`00499f18 App1!nl_C_LC_NUMERIC
00000000`00499f88 App1!nl_C_LC_TIME
00000000`0049aec0 App1!nl_C_LC_COLLATE
00000000`00499d58 App1!nl_C_LC_MONETARY
00000000`00499ce0 App1!nl_C_LC_MESSAGES
00000000`0049a9e0 App1!nl_C_LC_PAPER
```

```
00000000`0049aa38 App1!nl_C_NAME
00000000`0049aac0 App1!nl_C_ADDRESS
00000000`0049ab98 App1!nl_C_TELEPHONE
00000000`0049ac10 App1!nl_C_MEASUREMENT
00000000`0049ad08 App1!nl_C_IDENTIFICATION
00000000`0048d1c0 App1!nl_C_CTYPE_class+0x100
00000000`0048c2c0 App1!nl_C_CTYPE_tolower+0x200
00000000`0048c8c0 App1!nl_C_CTYPE_toupper+0x200
00000000`00497450 App1!nl_C_name
00000000`004975d0 App1!nl_C_locobj+0x158
00000000`00498850 App1!$d+0x30
00000000`00498850 App1!$d+0x30
00000000`00465268 App1!_libc_dlopen_mode
00000000`004651ec App1!_libc_dlsym
00000000`0046517c App1!_libc_dlclose
00000000`00465460 App1!dl_initial_error_catch_ts
00000000`0049b540 App1!nl_default_default_domain
00000000`0047e9e8 App1!_dlopen
00000000`0047ea3c App1!_dlclose
00000000`0047ea98 App1!_dlsym
00000000`0047eb4c App1!_dlvsym
00000000`00470f60 App1!_dlerror
00000000`00471324 App1!_dladdr
00000000`00471330 App1!_dladdr1
00000000`00471470 App1!_dlinfo
00000000`00471528 App1!_dlmopen
00000000`004d1078 App1!dl_pagesize
00000000`004a1e68 App1!_EH_FRAME_BEGIN_
00000000`004cfb20 App1!
00000000`004d5618 App1!static_map
00000000`00403f44 App1!_reclaim_stacks
00000000`004d1588 App1!object.6205
00000000`004d7d40 App1!_libc_multiple_threads
00000000`004d5a78 App1!static_slotinfo
00000000`004d78e0 App1!_fork_generation
00000000`004d6570 App1!fork_handler_pool+0x8
00000000`0048a618 App1!unsecure_envvars.10865+0x118
00000000`004046f0 App1!_wait_lookup_done
00000000`00400040 App1+0x40
????????`????????
```

13. Explore the contents of memory pointed to by *App1!memalign_hook_ini* and *App1!_progname* addresses:

```
0:001> u 00000000`0041cc00
App1!memalign_hook_ini:
00000000`0041cc00 a9b97bfd stp      fp,lr,[sp,#-0x70]!
00000000`0041cc04 910003fd mov      fp,sp
00000000`0041cc08 a9025bf5 stp      x21,x22,[sp,#0x20]
00000000`0041cc0c 900005b6 adrp    x22,App1!+0x18 (00000000`004d0000)
00000000`0041cc10 58004815 ldr      x21,App1!$d (00000000`0041d510)
00000000`0041cc14 911c62c2 add      x2,x22,#0x718
00000000`0041cc18 a90153f3 stp      x19,x20,[sp,#0x10]
00000000`0041cc1c a90363f7 stp      x23,x24,[sp,#0x30]
```

```
0:001> dp App1!_progname
00000000`004d1068 0000ffff`d30bf6dd 0000ffff`d30bf6db
00000000`004d1078 00000000`00010000 00000000`00000006
00000000`004d1088 00000000`00000000 00000000`00000000
00000000`004d1098 00000000`00000001 00000000`00000000
00000000`004d10a8 00000000`00000000 00000000`00000000
00000000`004d10b8 00000000`00000000 00000000`00000000
00000000`004d10c8 00000000`00000001 00000000`00000000
00000000`004d10d8 00000000`00000000 00000000`00000000
```

```
0:001> dc 0000ffff`d30bf6dd
0000ffff`d30bf6dd 31707041 47445800 5345535f 4e4f4953 App1.XDG_SESSION
0000ffff`d30bf6ed 3d44495f 30353836 534f4800 4d414e54 _ID=6850.HOSTNAME
0000ffff`d30bf6fd 6e693d45 6e617473 322d6563 31313230 E=instance-20211
0000ffff`d30bf70d 2d393031 34303032 4c455300 58554e49 109-2004.SELINUX
0000ffff`d30bf71d 4c4f525f 45525f45 53455551 3d444554 _ROLE_REQUESTED=
0000ffff`d30bf72d 52455400 74783d4d 2d6d7265 63363532 .TERM=xterm-256c
0000ffff`d30bf73d 726f6c6f 45485300 2f3d4c4c 2f6e6962 olor.SHLL=/bin/
0000ffff`d30bf74d 68736162 53494800 5a495354 30313d45 bash.HISTSIZE=10
```

```
0:001> da 0000ffff`d30bf6dd
0000ffff`d30bf6dd "App1"
```

```
0:001> db 0000ffff`d30bf6dd
0000ffff`d30bf6dd 41 70 70 31 00 58 44 47-5f 53 45 53 53 49 4f 4e App1.XDG_SESSION
0000ffff`d30bf6ed 5f 49 44 3d 36 38 35 30-00 48 4f 53 54 4e 41 4d _ID=6850.HOSTNAME
0000ffff`d30bf6fd 45 3d 69 6e 73 74 61 6e-63 65 2d 32 30 32 31 31 E=instance-20211
0000ffff`d30bf70d 31 30 39 2d 32 30 30 34-00 53 45 4c 49 4e 55 58 109-2004.SELINUX
0000ffff`d30bf71d 5f 52 4f 4c 45 5f 52 45-51 55 45 53 54 45 44 3d _ROLE_REQUESTED=
0000ffff`d30bf72d 00 54 45 52 4d 3d 78 74-65 72 6d 2d 32 35 36 63 .TERM=xterm-256c
0000ffff`d30bf73d 6f 6c 6f 72 00 53 48 45-4c 4c 3d 2f 62 69 6e 2f olor.SHLL=/bin/
0000ffff`d30bf74d 62 61 73 68 00 48 49 53-54 53 49 5a 45 3d 31 30 bash.HISTSIZE=10
```

Note: We see that a hook function is installed for *memalign* and *realloc*. Please find the following documentation for hook functions here:

https://www.gnu.org/software/libc/manual/html_node/Hooks-for-Malloc.html

14. Explore the contents of memory pointed to by *environ* variable:

```
0:001> dp environ
00000000`004d64c8 0000ffff`d30b8888 00000000`00000000
00000000`004d64d8 00000000`00000000 00000000`00000000
00000000`004d64e8 00000000`00000000 00000000`00000000
00000000`004d64f8 00000000`00000000 00000000`00000000
00000000`004d6508 00000000`00000000 00000000`00000000
```

```
00000000`004d6518 00000000`00000000 00000000`00000000  
00000000`004d6528 00000000`00000000 00000000`00000000  
00000000`004d6538 00000000`00000000 00000000`00000000
```

```
0:001> dp 0000ffff`d30b8888  
0000ffff`d30b8888 0000ffff`d30bf6e2 0000ffff`d30bf6f6  
0000ffff`d30b8898 0000ffff`d30bf716 0000ffff`d30bf72e  
0000ffff`d30b88a8 0000ffff`d30bf742 0000ffff`d30bf752  
0000ffff`d30b88b8 0000ffff`d30bf760 0000ffff`d30bf783  
0000ffff`d30b88c8 0000ffff`d30bf79e 0000ffff`d30bf7b1  
0000ffff`d30b88d8 0000ffff`d30bf7ba 0000ffff`d30bfe72  
0000ffff`d30b88e8 0000ffff`d30bfe8b 0000ffff`d30bfee5  
0000ffff`d30b88f8 0000ffff`d30bfeff 0000ffff`d30bff10
```

```
0:001> da 0000ffff`d30bf6e2  
0000ffff`d30bf6e2 "XDG_SESSION_ID=6850"
```

```
0:001> dpa 0000ffff`d30b8888  
0000ffff`d30b8888 0000ffff`d30bf6e2 "XDG_SESSION_ID=6850"  
0000ffff`d30b8890 0000ffff`d30bf6f6 "HOSTNAME=instance-20211109-2004"  
0000ffff`d30b8898 0000ffff`d30bf716 "SELINUX_ROLE_REQUESTED="  
0000ffff`d30b88a0 0000ffff`d30bf72e "TERM=xterm-256color"  
0000ffff`d30b88a8 0000ffff`d30bf742 "SHELL=/bin/bash"  
0000ffff`d30b88b0 0000ffff`d30bf752 "HISTSIZE=1000"  
0000ffff`d30b88b8 0000ffff`d30bf760 "SSH_CLIENT=37.228.238.120 61099 22"  
0000ffff`d30b88c0 0000ffff`d30bf783 "SELINUX_USE_CURRENT_RANGE="  
0000ffff`d30b88c8 0000ffff`d30bf79e "SSH_TTY=/dev/pts/1"  
0000ffff`d30b88d0 0000ffff`d30bf7b1 "USER=opc"  
0000ffff`d30b88d8 0000ffff`d30bf7ba "LS_COLORS=rs=0:di=38;5;27:ln=38;5;51:mh=44;38;5;15:pi=4"  
0000ffff`d30b88e0 0000ffff`d30bfe72 "MAIL=/var/spool/mail/opc"  
0000ffff`d30b88e8 0000ffff`d30bfe8b "PATH=/usr/local/bin:/usr/bin:/usr/local/sbin:/usr/sbin:"  
0000ffff`d30b88f0 0000ffff`d30bfee5 "PWD=/home/opc/ALCDA2/App1"  
0000ffff`d30b88f8 0000ffff`d30bfeff "LANG=en_US.UTF-8"  
0000ffff`d30b8900 0000ffff`d30bff10 "SELINUX_LEVEL_REQUESTED="
```

17. Now we look at how to perform a memory search.

```
0:000> s 0`004c0000 0`004f0000 6  
00000000`004c002a 06 9a 05 9b 04 9c 03 02-49 0a de dd dc db da d9 .....I.....  
00000000`004c007e 06 9a 05 45 95 0a 96 09-46 9b 04 9c 03 6c 0a de ...E....F....1..  
00000000`004c012d 06 00 00 00 41 0e a0 01-9d 14 9e 13 41 0d 1d 46 ....A.....A..F  
00000000`004c018d 06 9e 05 41 0d 1d 41 93-04 94 03 5b 0a de dd d4 ...A..A....[....  
00000000`004c020d 06 9e 05 41 0d 1d 41 93-04 94 03 5b 0a de dd d4 ...A..A....[....  
00000000`004c0285 06 9e 05 41 0d 1d 42 93-04 94 03 95 02 96 01 75 ...A..B.....u  
00000000`004c04fe 06 04 00 00 80 07 88 01-90 0b 00 b0 08 04 00 00 .....  
00000000`004cfe78 06 00 00 00 00 00 00-50 01 3a cd fc ff 00 00 .....P.:....  
00000000`004d0048 06 00 00 00 00 00 00-40 f1 34 cb fc ff 00 00 .....@.4....  
00000000`004d1080 06 00 00 00 00 00 00-00 00 00 00 00 00 00 00 00 .....  
00000000`004d7e00 06 00 00 00 00 00 00-00 00 00 00 00 00 00 00 00 .....
```

Note: It is possible to search through non-accessible regions as well; they are ignored:

```
0:000> s-q 0 Lffffff 6  
00000000`0048b208 00000000`00000006 00000000`0000006f  
00000000`0048be40 00000000`00000006 00000018`00000001  
00000000`0048bf28 00000000`00000006 00000018`00000001  
00000000`0048bfc0 00000000`00000006 00000018`00000001  
00000000`00499f50 00000000`00000006 00000000`00498240  
00000000`0049b728 00000000`00000006 00000000`00000002  
00000000`004cfe78 00000000`00000006 0000ffff`cd3a0150
```

```

00000000`004d0048 00000000`00000006 0000ffffc`cb34f140
00000000`004d1080 00000000`00000006 00000000`00000000
00000000`004d7e00 00000000`00000006 00000000`00000000
[...]

```

```

0:000> s-a 0000ffff`d30b88a8 L100000 "bin"
0000ffff`d30bf749 62 69 6e 2f 62 61 73 68-00 48 49 53 54 53 49 5a bin/bash.HISTSIZ
0000ffff`d30bfe9b 62 69 6e 3a 2f 75 73 72-2f 62 69 6e 3a 2f 75 73 bin:/usr/bin:/us
0000ffff`d30bfea4 62 69 6e 3a 2f 75 73 72-2f 6c 6f 63 61 6c 2f 73 bin:/usr/local/s
0000ffff`d30bfeb4 62 69 6e 3a 2f 75 73 72-2f 73 62 69 6e 3a 2f 68 bin:/usr/sbin:/h
0000ffff`d30bfebe 62 69 6e 3a 2f 68 6f 6d-65 2f 6f 70 63 2f 2e 6c bin:/home/opc/.l
0000ffff`d30bfed3 62 69 6e 3a 2f 68 6f 6d-65 2f 6f 70 63 2f 62 69 bin:/home/opc/bi
0000ffff`d30bfee1 62 69 6e 00 50 57 44 3d-2f 68 6f 6d 65 2f 6f 70 bin.PWD=/home/op
0000ffff`d30bffa5 62 69 6e 2f 6c 65 73 73-70 69 70 65 2e 73 68 20 bin/lesspipe.sh

```

Note: It is also possible to show all possible string fragments if any:

```

0:000> s-sa 0 Lfffffff
00000000`00400001 "ELF"
00000000`00400018 "D0@"
00000000`0040019c "GNU"
00000000`004001bc "GNU"
00000000`004001d1 "48y"
[...]
00000000`004a12b0 "weak version `"
00000000`004a12c0 "' not found (required by "
00000000`004a12e0 "version `"
00000000`004a12f0 "version lookup error"
00000000`004a1308 "cannot allocate version referenc"
00000000`004a1328 "e table"
00000000`004a1330 " of Verneed record"
00000000`004a1348 "RTLD_NEXT used in code not dynam"
00000000`004a1368 "ically loaded"
[...]
00000000`004d6588 "D?@"
00000000`004d7880 "@}M"
00000000`004d7d08 "xZM"
00000000`004d7d38 "peM"
00000000`01fa0700 "pnM"
00000000`01fa1680 "linux-vdso.so.1"
00000000`01fa16e0 "tls/atomics/"

```

15. Get the list of loaded modules:

```

0:001> lm
start           end             module name
00000000`00400000 00000000`004e0000  App1      T (service symbols: ELF Export Symbols)
c:\alcda2\app1\App1

```

```

0:001> lmv
start           end             module name
00000000`00400000 00000000`004e0000  App1      T (service symbols: ELF Export Symbols)
c:\alcda2\app1\App1
    Loaded symbol image file: App1
    Image path: /home/opc/ALCDA2/App1/App1
    Image name: App1
    Browse all global symbols functions data
    Timestamp:      unavailable (FFFFFFFFFF)
    CheckSum:       missing

```

```

ImageSize:          000E0000
Details:
0000ffff`cd3a0000 0000ffff`cd3b0000  linux_vdso_so T (service symbols: ELF In Memory Symbols)
    Loaded symbol image file: linux-vdso.so.1
    Image path: linux-vdso.so.1
    Image name: linux-vdso.so.1
    Browse all global symbols  functions  data
    Timestamp:      unavailable (FFFFFFFE)
    CheckSum:       missing
    ImageSize:      00010000
    Details:

```

Note: We don't see shared libraries except *vdso* (<https://man7.org/linux/man-pages/man7/vdso.7.html>) because they were statically linked. We also created the version of a dynamically linked *App1.shared* executable. If we load its core dump *App1.shared.core.22442* in the new instance of WinDbg Preview, we see the list of shared libraries:

```

Microsoft (R) Windows Debugger Version 10.0.25111.1000 AMD64
Copyright (c) Microsoft Corporation. All rights reserved.

```

```

Loading Dump File [C:\ALCDA2\A64\App1\App1.shared.core.22442]
64-bit machine not using 64-bit API

```

```

***** Path validation summary *****
Response           Time (ms)     Location
Deferred          srv*
Symbol search path is: srv*
Executable search path is:
Generic Unix Version 0 UP Free ARM 64-bit (AArch64)
Machine Name:
System Uptime: not available
Process Uptime: not available
.....
*** WARNING: Unable to verify timestamp for libc-2.17.so
libc_2_17!nanosleep+0x24:
0000ffff`0496dd64 d4000001 svc          #0

```

```

0:000> .sympath+ C:\ALCDA2\A64\App1
*** WARNING: Unable to verify timestamp for libc-2.17.so
Symbol search path is: srv*;C:\ALCDA2\A64\App1
Expanded Symbol search path is:
cache*;SRV*https://msdl.microsoft.com/download/symbols;c:\alcda2\a64\app1

```

```

***** Path validation summary *****
Response           Time (ms)     Location
Deferred          srv*
OK                C:\ALCDA2\A64\App1

```

```

0:000> .reload
....*** WARNING: Unable to verify timestamp for libc-2.17.so
.
```

```

***** Symbol Loading Error Summary *****
Module name        Error
libc-2.17          The system cannot find the file specified

```

You can troubleshoot most symbol related issues by turning on symbol loading diagnostics (!sym noisy) and repeating the command that caused symbols to be loaded. You should also verify that your symbol search path (.sympath) is correct.

```

0:000> lm
start          end            module name
00000000`00400000 00000000`00430000  App1      (service symbols: ELF Export Symbols)
c:\alcda2\alcd\app1\app1.shared
0000ffff`048c0000 0000ffff`04a50000  libc_2_17 T (service symbols: ELF In Memory Symbols)
0000ffff`04a50000 0000ffff`04a90000  libpthread_2_17 (deferred)
0000ffff`04ab0000 0000ffff`04ac0000  linux_vdso_so (deferred)
0000ffff`04ac0000 0000ffff`04b00000  ld_2_17 (deferred)

```

16. Disassemble the *bar_one* function and follow the indirect *sleep* function call:

```

0:000> uf bar_one
Couldn't resolve error at 'bar_one'

```

It looks like we need to dump the stack trace to have symbols fully loaded:

```

0:000> k
*** WARNING: Unable to verify timestamp for App1.shared
*** WARNING: Unable to verify timestamp for libpthread-2.17.so
# Child-SP      RetAddr           Call Site
00 0000ffff`048be750 0000ffff`0496da20  libc_2_17!nanosleep+0x24
01 0000ffff`048be790 00000000`00400738  libc_2_17!sleep+0x11c
02 0000ffff`048be990 00000000`0040074c  App1!bar_one+0x10
03 0000ffff`048be9a0 00000000`00400764  App1!foo_one+0xc
04 0000ffff`048be9b0 0000ffff`04a57d40  App1!thread_one+0x10
05 0000ffff`048be9d0 0000ffff`049a2d00  libpthread_2_17!pthread_get_minstack+0x1394
06 0000ffff`048beb00 ffffffff`fffffff    libc_2_17!clone+0x80
07 0000ffff`048beb00 00000000`00000000  0xffffffff`fffffff

```

```

0:000> uf bar_one
App1!bar_one:
00000000`00400728 a9bf7bfd stp      fp,lr,[sp,#-0x10]!
00000000`0040072c 910003fd mov      fp,sp
00000000`00400730 12800000 mov      w0,#-1
00000000`00400734 97ffff93 b1      App1!$x+0x30 (00000000`00400580)
00000000`00400738 a8c17bfd ldp      fp,lr,[sp],#0x10
00000000`0040073c d65f03c0 ret

```

```

0:000> u 00000000`00400580
App1!$x+0x30:
00000000`00400580 90000110 adrp      xip0,App1!+0x18 (00000000`00420000)
00000000`00400584 f9400611 ldr       xip1,[xip0,#8]
00000000`00400588 91002210 add      xip0,xip0,#8
00000000`0040058c d61f0220 br       xip1
00000000`00400590 90000110 adrp      xip0,App1!+0x18 (00000000`00420000)
00000000`00400594 f9400a11 ldr       xip1,[xip0,#0x10]
00000000`00400598 91004210 add      xip0,xip0,#0x10
00000000`0040059c d61f0220 br       xip1

```

Note: XIP0/XIP1 are mnemonics for X16/X17 registers used for inter-procedure-call.

```

0:000> dp 00000000`00420000 + 8
00000000`00420008 0000ffff`0496d904 0000ffff`04a57fd0
00000000`00420018 00000000`00400550 00000000`00400550
00000000`00420028 00000000`00000000 00000000`00000000
00000000`00420038 00000000`00000000 00000000`00000000
00000000`00420048 00000000`00000000 00000000`00000000
00000000`00420058 00000000`00000000 00000000`00000000

```

```

00000000`00420068 00000000`00000000 00000000`00000000
00000000`00420078 00000000`00000000 00000000`00000000

0:000> u 0000ffff`0496d904
libc_2_17!sleep:
0000ffff`0496d904 d106c3ff sub      sp,sp,#0x1B0
0000ffff`0496d908 a9b07bfd stp     fp,lr,[sp,#-0x50]!
0000ffff`0496d90c 910003fd mov     fp,sp
0000ffff`0496d910 a90153f3 stp     x19,x20,[sp,#0x10]
0000ffff`0496d914 a9025bf5 stp     x21,x22,[sp,#0x20]
0000ffff`0496d918 a90363f7 stp     x23,x24,[sp,#0x30]
0000ffff`0496d91c f90023f9 str     x25,[sp,#0x40]
0000ffff`0496d920 34000e40 cbz     w0,libc_2_17!sleep+0x1e4 (0000ffff`0496dae8)

```

```
0:000> ln 0000ffff`0496d904
```

Browse module
Set bu breakpoint

```
(0000ffff`0496d904)  libc_2_17!sleep
Exact matches:
libc_2_17!sleep = <no type information>
```

```

0:000> dps 00000000`00420000 + 8
00000000`00420008 0000ffff`0496d904 libc_2_17!sleep
00000000`00420010 0000ffff`04a57fd0 libpthread_2_17!pthread_create
00000000`00420018 00000000`00400550 App1!$x
00000000`00420020 00000000`00400550 App1!$x
00000000`00420028 00000000`00000000
00000000`00420030 00000000`00000000
00000000`00420038 00000000`00000000
00000000`00420040 00000000`00000000
00000000`00420048 00000000`00000000
00000000`00420050 00000000`00000000
00000000`00420058 00000000`00000000
00000000`00420060 00000000`00000000
00000000`00420068 00000000`00000000
00000000`00420070 00000000`00000000

```

17. *App1.shared.pmap.22442* also shows library memory regions:

```

22442: ./App1.shared
0000000000400000    64K r-x--  App1.shared
0000000004100000    64K r----  App1.shared
0000000004200000    64K rw---  App1.shared
0000000036a80000    192K rw---  [ anon ]
0000ffff02070000    64K ----- [ anon ]
0000ffff02080000   8192K rw---  [ anon ]
0000ffff02880000    64K ----- [ anon ]
0000ffff02890000   8192K rw---  [ anon ]
0000ffff03090000    64K ----- [ anon ]
0000ffff030a0000   8192K rw---  [ anon ]
0000ffff038a0000    64K ----- [ anon ]
0000ffff038b0000   8192K rw---  [ anon ]
0000ffff040b0000    64K ----- [ anon ]
0000ffff040c0000   8192K rw---  [ anon ]
0000ffff048c0000  1472K r-x--  libc-2.17.so
0000ffff04a30000    64K r----  libc-2.17.so
0000ffff04a40000    64K rw---  libc-2.17.so
0000ffff04a50000   128K r-x--  libpthread-2.17.so
0000ffff04a70000    64K r----  libpthread-2.17.so

```

```

0000ffff04a80000  64K rw--- libpthread-2.17.so
0000ffff04aa0000  64K r---- [ anon ]
0000ffff04ab0000  64K r-x-- [ anon ]
0000ffff04ac0000  128K r-x-- ld-2.17.so
0000ffff04ae0000  64K r---- ld-2.17.so
0000ffff04af0000  64K rw--- ld-2.17.so
0000ffffe2fc0000  192K rw--- [ stack ]
total                44096K

```

Note: We can also see shared library mappings in the output of the **!address** command:

```
0:000> !address
```

Mapping file section regions...
Mapping module regions...

BaseAddress	EndAddress+1	RegionSize	Type	State	Protect	Usage
+ 0`00000000	0`00400000	0`00400000				<unknown>
+ 0`00400000	0`00410000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_EXECUTE_READ	Image [App1;
"/home/opc/ALCDA2/App1/App1.shared"]						
+ 0`00410000	0`00420000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	Image [App1;
"/home/opc/ALCDA2/App1/App1.shared"]						
+ 0`00420000	0`00430000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	Image [App1;
"/home/opc/ALCDA2/App1/App1.shared"]						
+ 0`00430000	0`36480000	0`36650000				<unknown>
+ 0`36480000	0`364b0000	0`00030000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	<unknown> [.....Q.....]
+ 0`364b0000	fffff`02070000	ffffe`cb5c0000				<unknown>
+ ffff`02070000	fffff`02080000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	<unknown> [.....]
+ ffff`02080000	fffff`02880000	0`00800000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	<unknown> [.....]
+ ffff`02880000	fffff`02890000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	<unknown> [.....]
+ ffff`02890000	fffff`03090000	0`00800000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	<unknown> [.....]
+ ffff`03090000	fffff`030a0000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	<unknown> [.....]
+ ffff`030a0000	fffff`038a0000	0`00800000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	<unknown> [.....]
+ ffff`038a0000	fffff`038b0000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	<unknown> [.....]
+ ffff`038b0000	fffff`040b0000	0`00800000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	<unknown> [.....]
+ ffff`040b0000	fffff`040c0000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	<unknown> [.....]
+ ffff`040c0000	fffff`048c0000	0`00800000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	<unknown> [.....]
+ ffff`048c0000	fffff`04a30000	0`00170000	MEM_PRIVATE	MEM_COMMIT	PAGE_EXECUTE_READ	Image [libc_2_17; "/usr/lib64/libc-
2.17.so"]						
+ ffff`04a30000	fffff`04a40000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	Image [libc_2_17; "/usr/lib64/libc-
2.17.so"]						
+ ffff`04a40000	fffff`04a50000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	Image [libc_2_17; "/usr/lib64/libc-
2.17.so"]						
+ ffff`04a50000	fffff`04a70000	0`00020000	MEM_PRIVATE	MEM_COMMIT	PAGE_EXECUTE_READ	Image [libpthread_2_17;
"/usr/lib64/libpthread-2.17.so"]						
+ ffff`04a70000	fffff`04a80000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	Image [libpthread_2_17;
"/usr/lib64/libpthread-2.17.so"]						
+ ffff`04a80000	fffff`04a90000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	Image [libpthread_2_17;
"/usr/lib64/libpthread-2.17.so"]						
+ ffff`04a90000	fffff`04ab0000	0`00020000				<unknown>
+ ffff`04ab0000	fffff`04ac0000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_EXECUTE_READ	Image [linux_vdso_so; "linux-
vdso.so.1"]						
+ ffff`04ac0000	fffff`04ae0000	0`00020000	MEM_PRIVATE	MEM_COMMIT	PAGE_EXECUTE_READ	Image [ld_2_17; "/usr/lib64/ld-
2.17.so"]						
+ ffff`04ae0000	fffff`04af0000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READONLY	Image [ld_2_17; "/usr/lib64/ld-
2.17.so"]						
+ ffff`04af0000	fffff`04b00000	0`00010000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	Image [ld_2_17; "/usr/lib64/ld-
2.17.so"]						
+ ffff`04b00000	fffff`e2fc0000	0`de4c0000				<unknown>
+ ffff`e2fc0000	fffff`e2ff0000	0`00030000	MEM_PRIVATE	MEM_COMMIT	PAGE_READWRITE	<unknown> [.....]

18. We close logging before exiting WinDbg Preview:

```
0:000> .logclose
Closing open log file 'C:\ALCDA2\A64\App1\App1.log'
```

We recommend exiting WinDbg Preview app or WinDbg after each exercise to avoid glitches.